Philips
Fax with telephone and copier

Thermal Transfer

PPF591P



Philips Thermal Transfer fax

Philips Thermal Transfer fax machine with fashionable design. Furthermore this feature rich fax device is perfectly adapted to your needs.

Easy to use copier
- Multicopies up to 15 pages
- Prints in fine-/photo resolution

Plain paper fax
- Stores up to 15 pages
- Large capacity memory receive

Feature rich telephone
- Allows redial of last 10 numbers
- Chinese LCD display

PHILIPS

Fax with telephone and copier
Thermal Transfer

PPF591P/CNB

Specifications

Ink-film fax
- 10 page automatic doc feeder
- 9.600 bps modem speed: auto fall back
- Group broadcasting
- Horizontal resolution: 8 pixels/mm
- ITU Group 3 compatible: T.30 standard/T.30 new
- Memory: up to 15 pages
- Page header: automatic redial
- Paper tray up to 50 sheets
- Printing method: thermal transfer
- Timer function: send later
- Vertical resolution fine: 7.7 lines/mm
- Sending report: with reduced copy first page
- Vertical resolution standard: 3.85 lines/mm

Telephone
- Caller identification (CLIP)*
- Chain dialling
- Name dial entries:: 50
- On hook dialling
- Outgoing call log print
- Redial of the last 10 numbers
- Ringer melodies:: 10
- Short dial keys:: 10

Copier
- Fine-/photo-resolution
- Grey scales: 16
- Zoom-function (enlarge/reduce)
- Multicopy: up to 15 pages

Accessories
- Philips PFA 330: without PLUG'N'PRINT card / up to 110 pages A4

Dimensions
- Packed (WxDxH): 410 x 290 x 230 mm
- Unpacked: 318 x 210 x 150 mm

Power use
- Copy: typ 15 W
- Reception: typ 15 W
- Stand by: < 2 W
- Telephone conversation: typ 4 W
- Transmission: typ 15 W

Weight
- Packed (including country kit): 3.6 kg
- Unpacked (without accessories): 2.6 kg

Issue date 2014-02-13

Version: 1.0.1

12 NC: 8670 000 67006
EAN: 69 40971 30077 5

© 2014 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

* Depends on the availability of the service on the local operators network
* * Depends on the availability of caller identification