Data Sheet
FUJITSU Storage CELVIN® NAS QE705 Storage
Powerfull 2-Drive NAS

The CELVIN® NAS QE705 satisfies the business need for centralized data management needs. Both partners and users can set up and administrate the state of the art CELVIN® NAS easily and at an affordable price. Saving data, managing and sharing files over multiple platforms has never been so simple or so easy.



Business Server Feature
- 2 hot swappable drives
- Backup and replication center
- Multimedia features
- Multipurpose App center

Reliability
- Service-friendly cabinet
- 3-years spare part supply
- Country-specific warranty
- Top-up services are available

CELVIN® NAS QE705

Technical specifications	
	Firmware based on 4.1.4 Processor: Freescale™ ARM®v7 Cortex®-A9 dual-core 1.2GHz Memory: 512MB DRAM, 512 MB Flash Memory FAN: 1 x quiet cooling fan 70mm, 12V DC eSATA x1, USB3.0 x3, Gigabit LAN x2 Swappable trays x2
Hard disk capacity	Up to 2 x 3.5" or 2.5" SATA 3Gb/s or 6Gb/s HDD / SSD Up to 2x6TB raw capacity, consult HDD compatibiity list
System controls	Power, USB One-Touch-Copy, reset
Interfaces	
USB 3.0 total	Front: x1, Rear: x2
LAN / Ethernet	Rear side: x2 Gigabit RJ-45 Ethernet port (always on)
Software specification	
Networking	TCP/IP (IPv4 /IPv6 dual stack), multi IP setting,LACP, DHCP client, DHCP server including PXE boot CIFS/SMB(1.0,2.0,2.1 selectable), AFP/Netatalk3.2, NFS v3, HTTP, HTTPS, FTP,SFTP(admin), DDNS, NTP, Telnet, SSH, iSCSI, SNMP,WebDAV,SMSC Gigabit w/ Jumbo Frame, Bonjour iSCSI target (with multi-LUNs per target), Up to 256 LUNs/targets combined iSCSI LUN online expansion LUN mapping / LUN masking Online LUN capacity expansion SCSI Primary Commands -3 (SPC-3) support / persistent reservation iSCSI LUN Backup, One-time-Snapshot and Restore iSCSI initiator for virtual disks (max 8 disks); stack chaining master Virtual disk support for EXT3/ EXT4/ NTFS/ FAT32/ HFS+ iSCSI Connection and Management by Fujitsu Finder (Windows) VLAN 802.1Q USB WiFi-Adapter support IEEE 802.11b/g/n/ac WEP, WPA-personal (AES/TKIP), WPA2-personal (AES) Connection to wireless network or Ad Hoc network
Backup Management	Client backup software Time machine backup (OS X Lion support) 3rd party backup software support Encrypted block-level remote replication (instant, scheduled backup management); synchronization mode/Rsync Real-time remote replication (RTRR protocol) for real-time backup of server & client, 3 sync modes, filter, policy definition, SSL protected RTRR/Rsync work as server or client with bandwidth control Backup to Cloud Backup to (encryptable) USB/eSATA storage devices LUN backup and restore LUN point-in-time snapshot (1x)

Software specification

File System Management	Network share management '(max. 512 shares) Share folder level ACL support Unicode support Journaling file system File Station Supports ISO Mounting (Up to 256 ISO Files) Support thumbnail display of multimedia files Support share download link and upload link Drag-n-drop Files via Chrome and Firefox Browsers Photo, music, and video preview and playback File Compression and decompression (ZIP and 7z) Qsync Syncs files among multiple devices with SSL support Selective synchronization for syncing specific folders only Share team folder as a file center for team collaboration Shares files by links via e-mail Policy settings for conflicted files and file type filter support Incremental synchronization for HDD space saving Supports Windows & Mac OS
Disk Management	Disk usage status management; HDD S.M.A.R.T.; Bad blocks scan RAID 0,1, single disk, JBOD Built-in iSCSI target service, Virtual disks (iSCSI initiator) Online RAID management: expand capacity, migrate Raid-level, bitmap ISO mounting support up to 256 ISO-files
User Management	User quota management Windows Active Directory support, Domain Controller LDAP directory service supports Open LDAP User account management (max. 2048users) User group management (max. 256 groups) Shared folders (max. 256) Concurrent connections (max. 256) Support batch creating users User Import/ Export for Multiple CELVIN NAS Deployment Subfolder Permission (File/Directory ACL) Microsoft Networking (Samba) Host Access Control (Domain/IP)
VPN Server	OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption
System Tools	E-mail alert (SMTP authentication); SMS alert notification HDD standby mode Disk usage alert Automatic power on after power loss System firmware upgrade Back-up, restore, reset system settings Smart fan setting Configurable management port Policy-based unauthorized IP blocking; import user list Secure remote login by SSH connection Remote login by Telnet connection USB, SNMP v3, UPS support Scheduled power on/off Import SSL certificate Network recycle bin Password strength checker
Event Logs	Complete system logs (file level): system events management, connection logs, current connection of on-line users Centralized monitoring / syslog server (TCP / UDP) Manually and advanced log filtering via wizzard
Multilingual (Online) Support	Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, Turkish

Software specification	
FTP Server	FTP remote access (max. 256 concurrent connections) FTP with SSL/ TLS (explicit) mode FTP bandwidth control and connection control Passive FTP port range control FXP and Unicode support TFTP server (PXE boot) SFTP
Printer Server	Max. 3 printers; Internet Printing Protocol; Apple Bonjour Printing; Print Job display and management IP/Domain based privilge control
Web Server	Built-in editable php.ini, SQLite and MySQL Web-based management via phpMyAdmin Max. 32 virtual hosts
MySQL Server	MySQL database server
Security	Network access protection with autoblocking (SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP Policy based automatic IP blocking and IP filter Encrypted access (HTTPS, FTP with SSL/TLS(explicit),SSH/SFTP, RSync over SSH, CIFS host access control for shared folders ClamAV antivirus protection FIPS 140-2 validated AES 256-bit volume based data encryption Importable SSL certificates OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption; each 15 clients max. Radius Server Instant alert via E-mail, SMS, Instant Messaging, LCD
Surveillance Station	Includes 2 free camera licenses, up to 8 camera channels via additional license purchase Instant playback to check the recent event Visual aid by e-map Playback and speed control by shuttle bar Video preview on playback timeline Intelligent video analytics (IVA) for advanced video search

Software specification

Multimedia	DLNA Server Supports DLNA/UPnP TVs and Players such as PlayStation 3 and Xbox 360 Supported audio format: AIFF, APE, DSD (DSF, DFF), FLAC, M4A, M4A Apple Lossless (ALAC), MP3, Ogg Vorbis, WAV (PCM, LPCM), WMA, WMA PRO, WMA VBR *DRM encryption format is not supported. Support CUE indexing file for APE, FLAC audio format. Video and Audio On-the-fly Transcoding Video Station Show photos in thumbnails, list, timeline, or folder view Tags videos with text, color, and rating Animated thumbnails for videos Shares video collection link to social websites or through email Display movie information from IMDB Transcode Management Offline video transcoding: 240p, 360p, 480p, 720p and 1080p resolution Automatic video transcoding for watched folders Music Station Plays or Shares Music Collections with Web Browser Automatic Classification via Media Library Supported audio format: AIFF, APE, FLAC, M4A, M4A Apple Lossless (ALAC), MP3, Ogg Vorbis, WAV (PCM, LPCM),WMA, WMA PRO, WMA VBR * DRM encryption format is not supported. Internet Radio (MP3) Up to 8 Music Alarms Photo Station Show photos in thumbnails, list, timeline, or folder view Supports virtual/smart album Tags photos with text, color, and rating Slideshows with background music and different transition effects Animated thumbnails for videos Geotags photos and display them on Google maps Shares slideshows link to social websites or through email iTunes Server Audio and Video Sharing for Windows & Mac iTunes AirPlay Streams videos, photos and music from NAS to Apple TV via Qfile
Application center	Diverse applications downloadable via App center Fujitsu NAS Explorer, Fujitsu NAS Manager for Android / iOS
Download Station	PC-less BT, FTP/FTPS, and HTTP/HTTPS download (up to 500 Tasks) BT download with Magnet Link and PT support Scheduled download and bandwidth control RSS subscription and download (broadcatching) Bulk download with wildcard settings BT search Proxy support for BT download PC utility: Qget for downloads browsing and management
Browser Support	Internet Explorer 10+ / Mozilla Firefox 8, 9, 10 / Apple Safari 4, 5 / Google Chrome

Electrical values	
Device Classification	Information according to ErP Regulation (EC) No. 1275/2008 – Standby/networked standby requirements: All CELVIN® NAS Servers have a so called "EUP-mode" implemented. With activated "EuP-mode" the device has a maximum power consumption of 0.5 W in standby mode by limited functionality. (Details are described in the operating manual) The intended use of these type of networked infrastructure device is providing always available data access while operating (i.e. "always on"). The requirement of networked standby mode function as described in Regulation (EC) No. 1275/2008 Annex II, 3(b) ("Power management for networked equipment") would be inappropriate for this intended use of the equipment. It could only be achieved by turning off vital components of the equipment that are essential for the maintenance of the intended use.
Power consumption	Off-mode (EuP-mode): 0.3W HDD-Sleep mode: 9,8W HDD R/W-mode: 20,6 W
Power supply input	External power supply 100 - 240V
Power supply output	12V; 60W
Humidity (operating)	5 - 95 % (relative humidity), wet bulb 27° C
Compliance	
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	102 x 225 x 168.5 mm
Weight	1.28 kg
Operating ambient temperature	0 - 40 °C
Operating relative humidity	5 - 95 % (relative humidity), wet bulb 27° C
Package content	
	CELVIN NAS Server QE705; Power Cord,LAN cable, trays, Quick Start Guide, Service flyer

Order information

S26341-F106-L705	EAN: 4057185549271	w/o HDD EU
S26341-F106-L712	EAN: 4057185549318	2x2 TB NAS HDD EU
S26341-F106-L713	EAN: 4057185549356	2x3 TB NAS HDD EU
S26341-F106-L714	EAN: 4057185549394	2x4 TB NAS HDD EU
S26341-F106-L722	EAN: 4057185549431	2x2 TB NAS HDD INT
S26341-F106-L724	EAN: 4057185549479	2x4 TB NAS HDD INT
VFY:QE705XX020E1	EAN: 4057185578387	2x2TB NAS HDD EU
VFY:QE705XX030E1	EAN: 4057185578394	2x3TB NAS HDD EU
VFY:QE705XX040E1	EAN: 4057185578332	2x4TB NAS HDD EU

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Accessory CELVIN® NAS QE705, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about FUJITSU Storage CELVIN® NAS QE705, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2016-02-10 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH