WHI941ST

Wall mounted cooker hood



B

gorenje BY STARCK

- LedLight
- P.A.S. System
- Timer and refresh
- TouchFree coating
- AdaptTech

Freestanding wall hood
Venting with air extraction or recirculation
Energy class: **B**
Material of housing/chimney: **stainless steel and glass / stainless steel**
Colour of housing/chimney: **stainless steel**

Lightning efficiency class: **E**
Grease filtering efficiency class: **A**
Fluid dynamic efficiency class: **A**
Maximum extraction rate by extraction operation: **508 m³/h**
Maximum extraction rate by recirculation operation: **485 m³/h**
Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **250 m³/h**
Air flow by extraction version, step 2: **364 m³/h**
Air flow by extraction version, step 3: **508 m³/h**

AdaptTech: Automatic fan operation
Electronic control
Control setting: **Touch control**
Timer function
Number of speed positions: **3**

TouchFree Inox
Constant ventilation ReFresh
Lamp type: **Led strip**
On/off light switch
Number of lights: **1**
Air purifing function
Power of lights: **6 W**
Airflow boost position (PowerBoost 1) - extraction: **663 m³/h**
Airflow boost position (PowerBoost 2) - extraction: **732 m³/h**
Perimetric suction

Filter material: **Aluminium**
Grease filter indicator
Coal filter code (optional as separate purchase): **182183**
Motor type: **Capacitor motor**
Number of motors: **1**
Number of PowerBoost functions: **2**
No return airflow flap: **150 mm**

Noise level (max.): **59 dB(A)re 1 pW**
Height: **450 mm**
Min. height of the chimney: **1,060 mm**
Max. height of the chimney: **1,320 mm**
Annual energy consumption : **50.8 kWh**
Dimensions of the product (W×H×D): **90 × 45 × 47 cm**
Dimensions of packed product (W×H×D): **101.5 × 67.5 × 80.5 cm**
Net weight: **32 kg**
Gross weight: **36 kg**
Connected load: **284 W**
Code: **542086**
EAN code: **3838942104282**

http://www.gorenje.co.uk/product/542086