

Philips LED Inspection lamps
Multi-Directional Lighting System

1 module



LPL05SPAREX1

See better, work better

All-in-one lighting system for professionals

Robust and hands-free, this multidirectional module will provide you optimal visibility without shadow.

Optimal visibility, no shadow
- High-power LED light
- 300° rotating head
- Light output for one module: 120 lumens (normal mode)
- Light output for one module: 200 lumens (Boost mode)

Hands-free lighting
- 1 multidirectional module

High resistance
- Resistant to chemicals and workshop solvents
- Strong impact resistance -IK07
- Water and dust protected -IP54

High autonomy
- Fast Rechargeable, Energy saving LifeP04 battery technology

PHILIPS

Multi-Directional Lighting System
1 module

LPL05SPAREX1

Highlights

Light output for one module



Every module of the MDLS solution will provide a light output of 200 lumens in boost mode. In boost mode the light will last for 3 hours.

Light output for one module



Every module of the MDLS solution will provide you a light output of 120 lumens in normal mode. In normal mode the light will last for 5 hours.

Water and dust protected -IP54



The LED inspection lamp is water resistant and conforms to IP54.

Strong impact resistance -IK07



Strong impact resistance -IK07

300° rotating head



The 300° rotating head will enable you to achieve a shadow-free workspace for optimum safety and efficiency.

Fast Rechargeable



Fast Rechargeable, Energy saving LifeP04 battery technology. Since the modules are fast charging, whenever one of the modules is charged and ready for the job, you can take it out directly.

High-power LED light



As the international market leader in car lighting, we have years of experience and know-how in light. Philips LED inspection lamps are equipped with high power LEDs. Our LEDs combine strong light performance with a natural colour rendering for fatigue-free work.

Resistant to chemicals



As well as resisting knocks, the inspection lamp cases are resistant to water, chemicals and workshop solvents.

1 multidirectional module



1 multidirectional module

Multi-Directional Lighting System
1 module

LPL05SPAREX1

Specifications

Maximum visibility
- Light output: 120 lumens, 200 lumens

Robust
- Impact protection rating (IK): IK07
- Ingress protection ration (IP): IP54

Power
- Battery lifetime: up to 5 hr

Technical specifications
- Operating line voltage: 100-240 V

Outer Carton
- Number of consumer packages: 2
- Outer carton (L x W x H): 18.6 x 7.8 x 11.3 cm
- Gross weight: 0.7 kg
- EAN: 87 27900 38766 7

Issue date 2015-03-19

Version: 2.1.4

12 NC: 9237 956 90101
EAN: 87 27900 38766 7

© 2015 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com