ILP- Portable BT





	ILP-80 Portable BT	ILP-108 Portable BT
Resolution	203 DPI	
Printing method	Direct thermal	
Max. print speed	Max. 70 mm/sec	Max. 100 mm/sec
Max. print width	72 mm (4.25”)	108 mm (4.25”)
Max. paper length	1778mm (70”)	
Media type	Continuous, gap, black mark	
Media width	20mm ～ 76mm	40mm ～ 112mm
Media thickness	0,06mm ～ 0,254mm	
Label roll diameter	50mm	
Processor	32-bit CPU	
Memory	8MG Flash memory / 8MB SD RAM	
Interface	USB+Bluetooth	
Screen	OLED 1.3”	
Sensors	1: Gap sensor 2: Cover opening sensor 3: Black mark sensor	
Inernal fonts	8 Alpha-numeric bitmap fonts, Windows fonts are downloadable from software	
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST	
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Azgtec	
Rotation	0°, 90°, 180°, 270°	
Emulation	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS	
Printer head life	30 Km	
Operation system	Windows/Android/iOS	
SKD	Windows/Android/iOS	
Input/Output	Input: AC 100-240V,0.5A 50-60Hz; Output: DC 9V/2A	Input: AC 100-240V,0.5A 50-60Hz; Output: DC 5V/2A
Battery	7.4V/2500mAh	
Work environment	Temperature (5～40°C) humidity(25～85%)	
Storage environment	Temperature(-40～60℃) humidity(10～90%)	
Colour	Grey	
Weight	357 g.	583 g.
Dimensions	124x108x61mm (D×W×H)	150×131×64mm (D×W×H)
Warranty	3 years	