AEG

7000 Hob2Hood® 90 cm

DCE5960HM





The perfect partner when you cook
The 7000 Hob2Hood is a highly efficient feature that automatically controls your cooker hood and lights. Regardless of your hob temperature, the fan adjusts while you work, allowing you to fully concentrate on what you are cooking.

Product Benefits & Features

Hob2Hood. The hands-free hood
Hob2Hood automatically controls your cooker hood's power level and lights while you concentrate on the key moments of getting your dish just right.

- Electronic variable 3+Intensive speed push button control
- Washable aluminium grease filters
- Extraction mode
- Maximum recirculation rate of 290 m³/h
- 61 dB(A) noise level
- Recirculation or extraction options

Clean air. Faster.
This Cooker hood clears the kitchen from cooking fumes quickly. That is beacuse the advanced cooker hood has an effecient and powerful motor.



LEDlights for more refined cooking
Our LEDlights use far less energy than other lights, with a much longer life expectancy. And they provide expert illumination for greater detail while cooking.

Maximum filtration, again and again
A highly functioning filter that captures and removes fats and odours when cooking. The removable filter can be cleaned in the dishwasher, ensuring that your cooker hood is continually efficient.

One Touch. Complete Control
The full range of hood functions are consolidated into a single electronic control. Meaning settings can be monitored and adjusted with just one touch. Precisely and intuitively.

AEG

7000 Hob2Hood® 90 cm

DCE5960HM

Product Specification

Installation	Ceiling
Size	90
Dimensions, HxWxD	382-582x900x700
Minimum distance from electric cooking top	750
Minimum distance from gas cooking top	750
Cord Length (m)	1.1
Voltage (V)	230-240
Required Fuse	No
Frequency (Hz)	50
Colour	Stainless steel
Other comments technical specifications	Installation BIC with snpa in solution
Superperforming charcoal filter compatible	MCFB62, 902 980 207
Energy class	A
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filter efficiency class	D
Capacity minimum, m3/h	315
Capacity, Max m³/h	590
Capacity intensive, m3/h	710
Sound power min speed, dB(A)	54
Sound power max speed, dB(A)	63
Sound power intensive, dB(A)	67
No. of speed settings	3+Intensive
Lamp type	Dimmable LED stripe
No. of lamps	1
Grease filters	6
Recirc sound power min, dB(A)	56
Recirc sound power max, dB(A)	68
Recirculation min, m3/h	300
Recirculation max, m3/h	580

