SIKU INFRAPLATE PRO CLASSIC / SIKU INFRAPLATE PRO CLASSIC SLIM





The new SIKU Infraplate pro heating panels in timeless, slimline design. The heating panels are the most advanced solution for efficient, convenient and cost-effective heating of living areas.

PRODUCT DESCRIPTION

- clean, noiseless and dust-free room climate
- reduction of air circulation
- low acquisition and maintenance costs
- low space requirement
- easy wall or ceiling mounting
- longevity

TECHNICAL DATA

SURFACE	IR-coating
REAR MATERIAL	Clad steel sheet
FRAME	Aluminium white
HEATING ELEMENT	Carbon crystal
SURFACE TEMPERATURE	75-95°C
OVERHEATING PROTECTION	Yes
ELECTRICAL EFFICIENCY	98%
CABLE LENGTH	1,9 m
MOUNTING	Wall (WW) or ceiling (DW)
LED OPERATING LIGHT	Yes, only with wall-mounted types (WW)
WARRANTY	5 Years

WW indicates wall-mounted units.
DW indicates ceiling-mounted units.
When purchasing a „DW“ heating panel, the SIKU IPP-DAS ceiling mounting set or the IPP-chain will also be required as an accessory.

IP54

TECHNICAL DATA INFRAPLATE PRO CLASSIC

MODELS	DIMENSIONS (MM)	CURRENT	VOLTAGE 50 HZ	CURRENT	WEIGHT	CERTIFICATES	IP
SIKU IPP 160 WW	905x205x22	160W	230V	0,7 A	2 kg	RoHS, CE, TÜV GS	IP54
SIKU IPP 330 WW	1205x305x22	350W		1,5 A	3,35 kg	RoHS, CE, TÜV GS	
SIKU IPP 350 WW	605x605x22	350W		1,5 A	3,2 kg	RoHS, CE, TÜV GS	
SIKU IPP 580 WW	1005x605x22	580W		2,5 A	4,8 kg	RoHS, CE, TÜV GS	
SIKU IPP 700 WW	1205x605x22	700W		3,0 A	4,8 kg	RoHS, CE, TÜV GS	
SIKU IPP 900 WW	1205x755x22	900W		3,9 A	6,9 kg	RoHS, CE, TÜV GS	
SIKU IPP 280 DW	605x605x22	280W	230V	1,2 A	3,2 kg	RoHS, CE	IP54
SIKU IPP 450 DW	1005x605x22	450W		2,0 A	4,8 kg	RoHS, CE	
SIKU IPP 550 DW	1205x605x22	550W		2,4 A	5,6 kg	RoHS, CE	
SIKU IPP 700 DW	1205x755x22	700W		3,3 A	6,8 kg	RoHS, CE	

Printing errors, mistakes and technical changes reserved.

SIKU INFRAPLATE PRO CLASSIC DC





„DC“ - Direct Ceiling - stands for direct mounting on the ceiling through pre-drilled holes in the frame.

TECHNICAL DATA

SURFACE	Aluminium white
REAR MATERIAL	Clad steel sheet
FRAME	Aluminium
HEATING ELEMENT	NiCr-heating wire
SURFACE TEMPERATURE	approx. 130°C
OVERHEATING PROTECTION	Yes
ELECTRICAL EFFICIENCY	98%
CABLE LENGTH	1,9 m
MOUNTING	direct ceiling mounting (DC)
WARRANTY	2 years

IP52

TECHNICAL DATA INFRAPLATE PRO CLASSIC DC

MODELS	DIMENSIONS (MM)	CURRENT	VOLTAGE 50 HZ	CURRENT	WEIGHT	CERTIFICATES	IP
SIKU IPP 450 DC	630x630x21	450W	230V	1,96 A	3,6 kg	RoHS, CE, AA	IP52
SIKU IPP 700 DC	1030x630x21	700W		3,00 A	5,4 kg	RoHS, CE, AA	
SIKU IPP 900 DC	1230x630x21	900W		3,90 A	6,2 kg	RoHS, CE, AA	
SIKU IPP 1400 DC	1830x630x21	1400W		6,10 A	8,8 kg	RoHS, CE, AA	

AVAILABLE MODELS	ITEM NUMBER	PACKAGING UNIT
SIKU IPP 160 WW	(Item no. 50448)	4 Pcs
SIKU IPP 330 WW	(Item no. 50477)	4 Pcs
SIKU IPP 350 WW	(Item no. 50423)	4 Pcs
SIKU IPP 580 WW	(Item no. 50427)	4 Pcs
SIKU IPP 700 WW	(Item no. 50429)	4 Pcs
SIKU IPP 900 WW	(Item no. 50425)	4 Pcs
SIKU IPP 280 DW	(Item no. 50424)	4 Pcs
SIKU IPP 450 DW	(Item no. 50428)	4 Pcs
SIKU IPP 550 DW	(Item no. 50430)	4 Pcs
SIKU IPP 700 DW	(Item no. 50426)	4 Pcs
SIKU IPP 450 DC	(Item no. 50792)	4 Pcs
SIKU IPP 700 DC	(Item no. 50793)	4 Pcs
SIKU IPP 900 DC	(Item no. 50794)	4 Pcs
SIKU IPP 1400 DC	(Item no. 50795)	4 Pcs