Product specifications

Eaton FNQ-R-20

Catalog Number: FNQ-R-20

Eaton Bussmann series FNQ-R fuse, Current-limiting time-delay fuse, 20 A, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 300 Vdc|200 kAIC at 600 V, Melamine tube, 600 V, 300 Vdc



General specifications

Product Name	**Catalog Number**
Eaton Bussmann series FNQ-R fuse	FNQ-R-20
UPC	**EAN**
051712497121	5027590449717
Product Length/Depth	**Product Height**
0.41 in	1.5 in
Product Width	**Product Weight**
0.41 in	0.15 lb
Warranty	**Compliances**
Not Applicable	CE Marked RoHS Compliant

Powering Business Worldwide

Electrical Ratings

Amperage Rating

20 A

Voltage rating

600 Vac, 300 Vdc

General Information

Application

Line protection, small control transformers, industrial control, branch circuits

Connection

Ferrule end x ferrule end

Special features

Rejection style

Physical Details

Type

Current-limiting time-delay fuse

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - FNQ-R-20

Technical data sheets

FNQ-R-20~CLASS CC TIME DELAY REJECTION FUSE

Technical service bulletins

Datasheet - FNQ-30

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia