Alimentatore GX650 EVO





FEATURES

PSU GX650 EVO - SFX, 650W, 80Plus Gold, Fan FDB 92mm, Japan Capacitor, Modular

SPECIFICATIONS

Wattage	650W
ATX Version	V2. 31
Certification	80Plus® GOLD
PFC	Active
I/O switch	No
Power cord	Euro.1.5M (Safety)
Circuit	DC TO DC
Voltage	Full voltage 115~230V
Effeciency	Loading efficiency
	20% 87%
	50% 90%
	100% 87%
Connectors	24 Pin
	4x IDE Molex 4 Pin
	4x SATA
	2x MOBO (4+4P)
	2x (6+2P) + (6+2P)
	FDD
Cables	Full flat black cables
Modular cables	Full modular, free plug
Cable length (full modular)	1x 24P
	300MM (modular cables)
	2x (4P+4P)
	400MM (modular cables)
	2x (6+2)+(6+2)
	400+150MM (modular cables)
	1x 3 SATA+SATA
	445+150+150+150MM (modular cables)
	1x (4*IDE+FDD)
	445+150+150+150MM (modular cables)
Capacitors	Full Japanes Capacitors 105c
Fan	90mm Fan long life time use
Housing	Black non-scratch wrinkle finish
12v	Single rail
Fan speed	1800 R.P.M.
Protection	OVP / UVP / SCP / OPP / SCP
CE EMI	CE EMI
ErP	ErP Lot6
Dimension	125*100*62mm
N.W	1.51 KG
G.W	1.72 KG

PACKING INFORMATION

Code: **ITPSEGX650**
EAN: **8056157882374**

SOCIAL MEDIA COMMUNICATION

info@itekevo.com
www.itekevo.com