1000 Eaton Boulevard
Cleveland, OH 44122
United States

# Power Extension Cord, C19 to C20 - 16A, 250V, H05VV-F, 3 m (9.8 ft.), Black

MODEL NUMBER: **P036-03M-EU**



Connects high-output devices with C19/C20 power connectors, including routers and blade servers.

### Highlights

- Recommended for powering blade server chassis and other high-output devices
- 3-meter length allows flexibility in placing devices in relationship to AC outlet
- Ideal replacement for a worn-out or missing power extension cord
- VDE-compliant H05VV-F jacket allows use in European IT applications

### Package Includes

P036-03M-EU C19 to C20 Power Extension Cord, 3 m (9.8 ft.), Black

### Features

**Power Cord Connects High-Output Data Center Equipment to Reliable AC Power**
This VDE-compliant power cable connects a router, blade server or other high-output network device with a C20 power inlet to a PDU, UPS system or surge protector with C19 outlets. It can also extend an existing power connection up to three meters (9.8 feet). The P036-03M-EU features an IEC-320-C20 end for connecting to an AC power source or cord and an IEC-320-C19 end for connecting to a blade server chassis or other high-output device.

**H05VV-F Jacket Is Fully VDE-Compatible for European Applications**
The 0.75mm2 enhanced PVC jacket complies with VDE, CE and UKCA standards for data centers, racks, workstations and other IT applications in Europe.

## Specifications

| | |
|---|---|
| **OVERVIEW** | |
| UPC Code | 037332281036 |
| Product Type | Power Extension Cord |
| Device Compatibility | Network Switch; PDU; Router; Server; UPS |
| Country/Region | Europe |
| **INPUT** | |
| Maximum Input Amps | 16.0 |
| Voltage Compatibility (VAC) | 250 |
| **PHYSICAL** | |

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|---|---|
| Plug Color | Black |
| Cable Jacket Color | Black |
| Cable Jacket Material | PVC |
| Power Cord Jacket Type | H05VV-F |
| Cable Outer Diameter (OD) | 8.2 mm |
| Number of Conductors | 3 |
| Conductor Gauge | 48/0.2AS |
| Wire Gauge (AWG) | 16 |
| Wire Gauge (OD - $mm^2$) | 1.5 |
| Power Cord Color | Black |
| Cable Length (ft.) | 9.84 |
| Cable Length (m) | 3.00 |
| Shipping Dimensions (hwd / in.) | 10.00 x 7.99 x 0.50 |
| Shipping Dimensions (hwd / cm) | 25.40 x 20.29 x 1.27 |
| Shipping Weight (lbs.) | 0.89 |
| Shipping Weight (kg) | 0.40 |
| Unit Dimensions (hwd / in.) | 10.000 x 7.990 x 0.500 |
| **ENVIRONMENTAL** | |
| Operating Temperature Range | 5° to 158°F (-15° to 70°C) |
| Storage Temperature Range | 5° to 140°F (-15° to 60°C) |
| Operating Humidity Range | 20% TO 80% RH, NON-CONDENSING |
| Storage Humidity Range | 20% TO 80% RH, NON-CONDENSING |
| **CONNECTIONS** | |
| Side A - Connector 1 | IEC-320-C20 |
| Side B - Connector 1 | IEC-320-C19 |
| **FEATURES & SPECIFICATIONS** | |
| Antibacterial | No |
| Armored Cable | No |
| Angled Plug | No |
| High Voltage | Yes |
| Locking Plug | No |
| Coiled Power Cord | No |
| **STANDARDS & COMPLIANCE** | |

1000 Eaton Boulevard
Cleveland, OH 44122
United States

| | |
|---|---|
| Product Compliance | CE (Europe); REACH; RoHS; UKCA |
| **WARRANTY & SUPPORT** | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks are the property of their respective owners.