MPN: MO-E1MG-100FX-IR-OM

SFP 155 Mbps, SMF, 20 km, LC, DDMI, Compatible with Ruckus E1MG-100FX-IR-OM

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Ruckus Compatible**



Specifications

Features	**Brand compatibility**	Ruckus Wireless
	Certification	MSA
	Compatible products	Ruckus E1MG-100FX-IR-OM
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating relative humidity (H-H)**	10 - 80 %
	Operating temperature (T-T)	0 - 70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Packaging data	**Number of products included**	1 pc(s)
Performance	**Auto MDI/MDI-X**	Yes
	Cabling technology	100BASE-LX
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Ethernet interface type	Fast Ethernet
	Fiber optic connector	SFP
	Fiber ports quantity	1
	Interface type	LC
	Maximum data transfer rate	155 Mbit/s
	Maximum transfer distance	20000 m
	Multi-mode fiber (MMF) supported	No
	SFP transceiver standard	LX

Performance	**SFP transceiver type**	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Wavelength	1310 nm
Vendor information	**Brand Name**	Lanview
	Warranty	3 Year(s)

Other images

