

Plenum-Rated High-Speed HDMI Active Optical Cable with Detachable Connector

4K@60Hz UHD, HDMI Male to Micro HDMI Male (Type D) and Detachable HDMI Male (Type A), 50 m (164 ft.), CMP/CPR-certified, HEC, ARC, Gold-plated Contacts, Black

Part No.: 355698

EAN-13: 0766623355407 | UPC: 766623355407

HDMI Active Optical Cable - enjoy Ultra-High-Definition (UHD) performance over extra-long distances with flexible connections and no interference

The Manhattan Plenum-Rated High-Speed HDMI Active Optical Cable with Detachable Connector is the perfect solution for delivering an HDMI signal to a desired location such as a classroom, conference room, healthcare facility, trade show or another commercial environment. Active Optical Cable (AOC) technology offers several advantages over standard HDMI cables. Its smaller cable diameter ensures greater flexibility and maneuverability during installation into tight spaces and features a Micro HDMI type-D connector for a narrower connection through walls. You can attach the included HDMI type-A adapter for your traditional, full-scale source-to-display connection and enjoy your videos in ultra-sharp, smooth 4K@60Hz. Its construction from fiber strands eliminates the risk of electromagnetic/radio frequency interference to give the best performance, stability and reliability when is use. The AOC is an excellent choice for high-interference environments such as data centers, surgical theaters, DJ events or manufacturing facilities where high resolution and consistent display are critical.

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Features:

- Extends an HDMI signal over long distances without an external repeater, signal loss or interference
- Extends an HDMI signal over long distances without an external repeater, signal loss or interference
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- Extends an HDMI signal over long distances without an external repeater, signal loss or interference
- Standard HDMI connector (type A) to Micro HDMI (type D) for a narrower connection through walls; includes HDMI type-A adapter for traditional source-to-display connection
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- Immune to EMI (electromagnetic interference) and RFI (radio frequency interference)
- Standard HDMI connector (type A) to Micro HDMI (type D) for a narrower connection through walls; includes HDMI type-A adapter for traditional source-to-display connection
- Gold-plated contacts for corrosion-free connections
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces
- Supports HDMI Ethernet Channel (HEC)
- Standard HDMI connector (type A) to Micro HDMI (type D) for a narrower connection through walls; includes HDMI type-A adapter for traditional source-to-display connection
- Supports HDCP 2.2, CEC and ARC
- Immune to EMI (electromagnetic interference) and RFI (radio frequency interference)
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- Standard HDMI connector (type A) to Micro HDMI (type D) for a narrower connection through walls; includes HDMI type-A adapter for traditional source-to-display connection
- Supports bandwidth up to 18 Gbps
- Gold-plated contacts for corrosion-free connections
- CMP/CPR (plenum) rated
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Plug and Play; requires no external power supply
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Built-in, active amplifier circuitry
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- Three-year warranty
- Supports HDMI Ethernet Channel (HEC)
- Immune to EMI (electromagnetic interference) and RFI (radio frequency interference)
- Supports HDCP 2.2, CEC and ARC
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- Gold-plated contacts for corrosion-free connections
- Supports bandwidth up to 18 Gbps
- Supports Ultra-High-Definition (UHD) 4K@60Hz 4:4:4 chroma subsampling
- CMP/CPR (plenum) rated
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Plug and Play; requires no external power supply
- Immune to EMI (electromagnetic interference) and RFI (radio frequency interference)
- Built-in, active amplifier circuitry
- Supports HDMI Ethernet Channel (HEC)
- Three-year warranty
- Gold-plated contacts for corrosion-free connections
- Supports HDCP 2.2, CEC and ARC
- Standard HDMI connector (type A) to Micro HDMI (type D) for a narrower connection through walls; includes HDMI type-A adapter for traditional source-to-display connection
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Supports bandwidth up to 18 Gbps
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces
- CMP/CPR (plenum) rated
- Supports HDMI Ethernet Channel (HEC)
- Plug and Play; requires no external power supply
- Fiber and copper-wire hybrid for a thinner cable; ideal for in-wall installations and narrow spaces
- Built-in, active amplifier circuitry
- Immune to EMI (electromagnetic interference) and RFI (radio frequency interference)
- Three-year warranty
- Supports HDCP 2.2, CEC and ARC
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- Immune to EMI (electromagnetic interference) and RFI (radio frequency

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

interference)
- Supports bandwidth up to 18 Gbps
- Gold-plated contacts for corrosion-free connections
- CMP/CPR (plenum) rated
- Gold-plated contacts for corrosion-free connections
- Plug and Play; requires no external power supply
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Built-in, active amplifier circuitry
- High Dynamic Range (HDR) for superior contrast and brilliant colors
- Three-year warranty
- Supports HDMI Ethernet Channel (HEC)
- Supports HDMI Ethernet Channel (HEC)
- Supports HDCP 2.2, CEC and ARC
- Supports HDCP 2.2, CEC and ARC
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- Compatible with Dolby, Dolby Atmos, DTS and PCM audio formats
- Supports bandwidth up to 18 Gbps
- Supports bandwidth up to 18 Gbps
- CMP/CPR (plenum) rated
- CMP/CPR (plenum) rated
- Plug and Play; requires no external power supply
- Plug and Play; requires no external power supply
- Built-in, active amplifier circuitry
- Built-in, active amplifier circuitry
- Three-year warranty

Specifications:

Standards and Certifications
• RoHS
• CE
• FCC
• CMP/CPR (plenum) rated

General
• Fiber: OM3
• 4K (3840 × 2160) at 60 Hz resolution
• Bandwidth: 18 Gbps
• HDCP 2.2 support
• CEC support
• HDR support
• ARC support
• Length: 50 m (164 ft.)
• Weight: 1.5 g (3.31 lbs.)

Chipsets
• Output: SL82817

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Input: SL82827
- VCSEL II-VI
- Operating voltage: 5 V
- Operating current: 50 mA
- Power consumption: 250 mW

Connectors
- One HDMI 19-pin male, type A
- One Micro HDMI 19-pin male, type D (with detachable HDMI 19-pin male adapter, type A)
- USB Micro-B input: DC 5 V (optional)
- Gold-plated contacts
- Zinc diecast connectors

Cable
- 28 AWG cable
- OD: 4.5 mm, ± 0.2 mm
- Bend radius: 20 mm
- Fiber pulling/tensile strength: 25 kg (250 N)

Operating Environment
- Operation temperature: 0 - 75°C (32 - 167°F)
- Storage temperature: -20 - 70°C (-4 - 158°F)
- Humidity (noncondensing): 10 - 85%

Package Contents
- Plenum-Rated High-Speed HDMI Active Optical Cable with Detachable Connector
- USB Micro-B male to USB-A male power cable, 1m (3.3 ft.)



For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.









For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.