MPN: MO-G-SFP-BX-U-20KM

# SFP 1.25 Gbps, SMF, 20 km, LC, DOM support, Compatible with Generic SFP-BX-U-20KM

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Generic Compatible**



## Specifications

| | | |
|---|---|---|
| **Features** | **Certification** | MSA |
| | **Compatible products** | Generic SFP-BX-U-20KM |
| | **Easy to install** | Yes |
| | **Form factor** | SFP |
| | **Plug and Play** | Yes |
| | **RoHS compliance** | Yes |
| **Operational conditions** | **Operating temperature (T-T)** | 0-70 °C |
| | **Storage relative humidity (H-H)** | 10-85 % |
| | **Storage temperature (T-T)** | -40-85 °C |
| **Performance** | **Duplex system** | Half |
| | **Ethernet interface type** | Gigabit Ethernet |
| | **Fiber cable diameters supported (core/cladding)** | 9/125, 9/128 µm |
| | **Fiber optic connector** | SFP |
| | **Interface type** | LC |
| | **Maximum data transfer rate** | 1000 Mbit/s |
| | **Maximum transfer distance** | 20000 m |
| | **Maximum transfer distance (Single-mode)** | 20000 m |
| | **Multi-mode fiber (MMF) supported** | No |
| | **Rx wavelength (max)** | 1550 nm |
| | **SFP transceiver standard** | BX-U |
| | **SFP transceiver type** | Fiber optic |
| | **Single-mode fiber (SMF) supported** | Yes |

| | | |
|---|---|---|
| **Performance** | **Tx wavelength (max)** | 1310 nm |
| **Vendor information** | **Brand Name** | Lanview |
| | **Warranty** | 5 Year(s) |
| **Weight & dimensions** | **Package type** | White box |

## Other images

