MPN: MO-G-SFP-BX-U-3KM

SFP 1.25 Gbps, SMF, 2 km, LC, DDMI, Compatible with Generic SFP-BX-U-3KM

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Generic Compatible**



Specifications

Features	**Certification**	MSA
	Compatible products	Generic SFP-BX-U-3KM
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating temperature (T-T)**	0-70 °C
	Storage relative humidity (H-H)	10-85 %
	Storage temperature (T-T)	-40-85 °C
Performance	**Cabling technology**	1000BASE-BX10-U
	Ethernet interface type	Gigabit Ethernet
	Fiber cable diameters supported (core/cladding)	9/125, 9/128 µm
	Fiber ethernet cabling technology	1000BASE-BX
	Fiber optic connector	SFP
	Interface type	LC
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	3000 m
	Multi-mode fiber (MMF) supported	No
	SFP transceiver standard	BX-U
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Wavelength	1310 nm
Vendor information	**Brand Name**	Lanview

Vendor information	**Warranty**	5 Year(s)
Weight & dimensions	**Package type**	White box

Other images

