MPN: MO-SFP-GIG-BX-D

SFP 1 Gbps, SMF, 10 km, LC, DOM support, Compatible with Alcatel-Lucent SFP-GIG-BX-D

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Alcatel-Lucent Compatible**



Specifications

Features	**Brand compatibility**	Alcatel-Lucent
	Certification	MSA
	Compatible products	Alcatel-Lucent SFP-GIG-BX-D
	Easy to install	Yes
	Hot-Plug support	Yes
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating relative humidity (H-H)**	10 - 80 %
	Operating temperature (T-T)	0 - 70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Packaging data	**Number of products included**	1 pc(s)
Performance	**Auto MDI/MDI-X**	Yes
	Cabling technology	1000BASE-BX10-D
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber cable diameters supported (core/cladding)	9/125 µm
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (min)	1310 nm

Performance	**SFP transceiver standard**	BX
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Tx wavelength (min)	1490 nm
Vendor information	**Brand Name**	Lanview
	Warranty	3 Year(s)
Weight & dimensions	**Package type**	White box

Other products in this series

Brand compatibility	1000BASE-BX10-D	1000BASE-BX10-U	1000BASE-EX	1000BASE-LX
Alcatel-Lucent	MO-SFP-GIG-BX-D	MO-SFP-GIG-BX-U	MO-SFP-GIG-LH40	MO-SFP-GIG-LX
Allied Telesis				

Brand compatibility	1000BASE-SX	1000BASE-T	1000BASE-ZX	100BASE-EX
Alcatel-Lucent	MO-SFP-GIG-SX	MO-SFP-GIG-T	MO-GLC-ZX-SMD	MO-SFP-100-LC-SM40
Allied Telesis				

Brand compatibility	100BASE-FX	10GBase-ER	10GBase-LR	10GBASE-LRM
Alcatel-Lucent	MO-SFP-100-LC-MM	MO-SFP-AL-10G-ER		MO-AL-SFP-10G-LRM
Allied Telesis			MO-AT-SP10LR	

Brand compatibility	10GBASE-SR
Alcatel-Lucent	MO-SFP-10G-SR-AL
Allied Telesis	

Other images

