MPN: MO-AT-SPFXBD-LC-15

SFP 155 Mbps, SMF, 20 km, DDMI Support, Compatible with Allied Telesis AT-SPFXBD-LC-15

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Cisco Compatible**



Specifications

Features	**Brand compatibility**	Allied Telesis
	Certification	MSA
	Compatible products	Allied Telesis AT-SPFXBD-LC-15
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating temperature (T-T)**	0-70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Packaging data	**Number of products included**	1 pc(s)
Performance	**Cabling technology**	100BASE-BX10-D
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	SFP
	Maximum data transfer rate	155 Mbit/s
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (min)	1310 nm
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes

Performance	**Tx wavelength (min)**	1550 nm
Vendor information	**Brand Name**	Lanview
	Warranty	5 Year(s)
Weight & dimensions	**Package type**	White Box

Other images

