MPN: MO-ENT-MGBIC-LC03

SFP 1.25 Gbps, MMF, 2 km, LC, DDMI, Compatible with Enterarsys MGBIC-LC03

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Enterarsys Compatible**



Specifications

Features	**Certification**	MSA
	Compatible products	Enterarsys MGBIC-LC03
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Maximum operating temperature**	70 °C
	Minimum operating temperature	0 °C
	Operating temperature (T-T)	0-70 °C
	Storage relative humidity (H-H)	10 - 85 %
	Storage temperature (T-T)	-40 - 85 °C
Other features	**RX sensitivity**	-18 dB
Packaging data	**Number of products included**	1 pc(s)
Performance	**Cabling technology**	1GBASE-LX
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Ethernet interface type	Gigabit Ethernet
	Fiber ethernet cabling technology	1000BASE-LX
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	LC
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	2000 m

Performance	**Multi-mode fiber (MMF) supported**	No
	SFP transceiver standard	LX
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes
	Tx power (max)	4 dBmW
	Tx power (min)	-9 dBmW
	Wavelength	1310 nm
Vendor information	**Brand Name**	Lanview
	Warranty	5 Year(s)
Weight & dimensions	**Package type**	White Box

Other images

