MPN: MO-ENT-MGBIC-BX10-D

SFP 1.25 Gbps, SMF, 20 km, LC, DOM support, Compatible with Enterasys MGBIC-BX10-D

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Enterasys Compatible**



Specifications

Features	**Certification**	MSA
	Compatible products	Enterarsys MGBIC-BX10-D
	Easy to install	Yes
	Form factor	SFP
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating temperature (T-T)**	0-70 °C
	Storage relative humidity (H-H)	10-85 %
	Storage temperature (T-T)	-40-85 °C
Performance	**Duplex system**	Half
	Ethernet interface type	Gigabit Ethernet
	Fiber cable diameters supported (core/cladding)	9/125, 9/128 µm
	Fiber optic connector	SFP
	Interface type	LC
	Maximum data transfer rate	1000 Mbit/s
	Maximum transfer distance	20000 m
	Maximum transfer distance (Single-mode)	20000 m
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (max)	1310 nm
	SFP transceiver standard	BX-D
	SFP transceiver type	Fiber optic
	Single-mode fiber (SMF) supported	Yes

Performance	**Tx wavelength (max)**	1490 nm
	Wavelength	1490 nm
Vendor information	**Brand Name**	Lanview
	Warranty	3 Year(s)
Weight & dimensions	**Package type**	White Box

Other images

