MPN: MO-ENT-10GB-BX10-U

SFP+ BX-U 10 Gbps, SMF, 10 km, LC, Compatible with Enterarsys 10GB-BX10-U

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **100% Enterarsy Compatible**



Specifications

Features	**Certification**	MSA
	Compatible products	Enterarsys 10GB-BX10-U
	Easy to install	Yes
	Form factor	SFP+
	Hot-Plug support	Yes
	Hot-swap	Yes
	Plug and Play	Yes
	RoHS compliance	Yes
Operational conditions	**Operating temperature (T-T)**	0-70 °C
	Storage relative humidity (H-H)	10-85 %
Performance	**Cabling technology**	10GBASE-BX10-U
	Digital Diagnostics Monitoring (DDM)	Yes
	Duplex system	Full
	Fiber cable diameters supported (core/cladding)	9/125 µm
	Fiber optic connector	LC
	Fiber ports quantity	1
	Interface type	SFP+
	Maximum data transfer rate	10000 Mbit/s
	Maximum transfer distance	10000 m
	Multi-mode fiber (MMF) supported	No
	Rx wavelength (max)	1330 nm
	SFP transceiver standard	BX-U
	SFP transceiver type	Fiber optic

Performance	**Single-mode fiber (SMF) supported**	Yes
	Tx wavelength (max)	1270 nm
	Wavelength	1270 nm
Vendor information	**Brand Name**	Lanview
	Warranty	5 Year(s)
Weight & dimensions	**Package type**	White Box

Other images

