

Essential Mini Flood G2

BVP152 LED9/WW 120-277V 10W SWB CE

10 W, Black

The Essential Mini Flood G2 is a highly efficient LED floodlight at a very competitive price. It is an ideal replacement for conventional halogen floodlights with substantial energy savings. Its design with curved edges makes it stand out, while its robustness ensures a long life of great lighting. It has a very smooth even light output with less glare.

Warnings and Safety

- Install according to appropriate norms/regulations for your country

Product data

General Information	
Lamp family code	-
Light source replaceable	No
Driver included	Yes

Light Technical	
Luminous Flux	950 lumen
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	95 lm/W
Color rendering index (CRI)	>80
Luminaire light beam spread	80°

Operating and Electrical	
Input Voltage	120 to 277 V
Line Frequency	50 to 60 Hz
Inrush current	3.6 A
Inrush time	0.0476 ms
Power Consumption	10 W
Power Factor (Fraction)	0.5
Connection	Flying leads/wires
Cable	Cable 0.3 m without plug
Number of products on MCB of 16 A type B	95

Temperature	
Ambient temperature range	-25 to +40 °C

Essential Mini Flood G2

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing	
Housing Material	Aluminum die cast
Housing Color	Black
Mounting device	Mounting bracket adjustable
Overall length	109 mm
Overall height	30 mm
Effective projected area	0.014 m²

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	Philips standard surge protection level
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Median useful life L70B50	30,000 hour(s)

Product Data	
Full product code	871016334999299
Order product name	BVP152 LED9/WW 120-277V 10W SWB CE
Order code	911401841180
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	18
Material Nr. (12NC)	911401841180
Full product name	BVP152 LED9/WW 120-277V 10W SWB CE
EAN/UPC - Case	8710163350103
EAN/UPC - Product/Case	8710163349992

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.