

3 m LC to LC UPC Fiber Optic Patch Cable, Uniboot Pull-push tab, 2.0 mm, Duplex, OFNR, OM4 Multimode, Aqua

50/125 µm, Bend Insensitive Multimode Fiber (BIMMF), 9.8 ft

Part No.: 752589

EAN-13: 0766623752589 | UPC: 766623752589

Enjoy unparalleled connectivity with our cutting-edge fiber optic solutions.

Our adaptable connectivity options are the perfect choice for interconnect and cross-connect applications, and they are designed to deliver optimal performance in telecommunications rooms, data centers, entrance facilities, and even at the desk. Our UPC (Ultra Physical Contact) fiber connectors guarantee a superior surface finish and improved return loss, thereby improving the overall quality of your network.

The uniboot push-pull tab design in fiber optic cables allows for easy insertion and removal in high-density cabling environments without requiring special tools, while also reducing cable clutter and simplifying installation and maintenance.

Our OM4 multimode fiber cables are perfect for high-speed network connections, providing outstanding performance and reliability. These cables are designed for short to medium-range applications and are optimized to support 10G, 40G, and 100G Ethernet, making them ideal for data center environments. With their high bandwidth capabilities and low signal attenuation, OM4 fiber optics ensure efficient data transmission for demanding network infrastructures. Additionally, the bend-insensitive design reduces attenuation when the cables are twisted or bent, enhancing installation and maintenance efficiency.

For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Our cables are designed to provide exceptional performance characteristics, such as high bandwidth and low attenuation, which are critical for long-distance and high-speed communication. They are made from Corning optical fiber ultra-pure glass. Finally, our products are backed by a lifetime warranty, which guarantees that your investment will be safeguarded for years to come. For dependable, high-performance connectivity that endures the test of time, select our fiber optic solutions.

Features:

- Versatile Connectivity: Ideal for interconnect and cross-connect applications in entrance facilities, telecommunications rooms, data centers, and at the desk.
- UPC (Ultra Physical Contact) fiber connectors for a better surface finish and improved return loss.
- Uniboot allows one cable to carry two fibers, reducing the cable bulk when routing.
- In high-density spaces, a push-pull tab enables speedy plugging without the use of any tools.
- OM4 Multimode Fiber: Employs OM4 multimode fiber, delivering superior bandwidth and exceptional performance for extended-range, ultra-high-speed data transmission in advanced enterprise and large-scale data center networks.
- Low signal loss and high data rate - perfect for use in 40G Ethernet applications and beyond.
- Bend Insensitive Design: Features bend insensitive technology, reducing attenuation when bent or twisted, which enhances installation and maintenance efficiency
- Made from Corning optical fiber ultra-pure glass - Corning glass fiber optic cables offer excellent performance characteristics, including low attenuation and high bandwidth, which are crucial for high-speed and long-distance communication.
- Each cable ships with the test report included
- Lifetime Warranty

Specifications:

Connector type: LC UPC Duplex to LC UPC Duplex
Fiber count: 2 Fibers
Bend Radius: 45 mm
Fiber mode: Multi Mode OM4 50/125µm
Wavelength: 850/1310nm
Polarity: A (Tx) to B (Rx)
Cable outer diameter (OD): 2.0mm
Cable jacket: Riser (OFNR)

For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.


Ferrule material: Ceramic (zirconia)
Insertion loss: typical ≤0.2dB
Return loss: ≥20dB
Attenuation @ 850 / 1300 nm (dB/km): ≤ 3,2 / ≤ 0,8
Connector durability: 1000 insertion - extraction cycles min.
Operation temperature range: -20°C to +75°C











For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.



For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.