Powering Business Worldwide

pe.eaton.com



Eaton FERRUPS UPS

FL340AA0A0A0A0B

UPC:743172067203

Dimensions:

- **Height:** 40 IN
- **Length:** 35 IN
- **Width:** 22 IN

Weight:450 LB

Warranties:

- 2 year

Specifications:

- **Special Features:** AVR/DVR (recommended for PFC loads)
- **Type:** UPS
- **Input Connection:** Fixed connection
- **Input Voltage Range:** 240V
- **Input Frequency Range:** 60 Hz
- **Input Power Factor:** 0.98
- **Receptacle:** None/Hardwired
- **Output Waveform:** Sine wave
- **Voltage:** 120/240V
- **Output Voltage Range:** ± 3% for input voltages of +15 to -20%
- **Battery Type:** External battery, standard charger
- **Communication:** RS-232 (DB-25)
- **Software Compatibility:** Intelligent Power Software Suite
- **User Interface:** On/off switch, alarm switch, 5 front indicator lights
- **Relative Humidity:** 5-90% non-condensing
- **Temperature Range:** 0° to 40°C (32° to 104°F)

Supporting documents:

- Eaton FERRUPS UPS

- Eaton Specification Sheet - FL340AA0A0A0A0B

Certifications:

- EN 62040-2
- ANSI/IEEE Std C62.45
- CSA Certified
- UL Listed
- ANSI/IEEE Std C62.41
- FCC Cat. A

Product compliance: No Data

© 2016 Eaton. All rights reserved.