# OZUL10BE 90W USB PD Charger

## Product Images








## Short Description

- **Charging Technology:** High-Power GaN Technology, USB Power Delivery (PD) 3.0, and PPS.

- **Total Power Output:** Max. 90W.
- **Output Specifications:** DC 5.0V to 20.0V.
- **Device Compatibility:** Flagship smartphones, high-performance tablets, and laptops.
- **Included Accessories:** Built-in 1.2m USB-C cable and detachable 1.2m AC power cable.
- **Safety Features:** Built-in protection against overload, short-circuiting, and overheating.

## Description

The Conceptronic OZUL10BE 90W USB PD Charger is designed to deliver fast, efficient, and reliable power for a wide range of USB-C devices. Featuring USB Power Delivery (PD) 3.0 technology, it enables high-speed charging to keep your devices powered throughout the day, whether at home, in the office, or on the go.

With up to 90W output, it is suitable for charging higher-power laptops such as MacBook Pro, Dell XPS 15, and Lenovo ThinkPad series, as well as tablets like iPad Pro and smartphones including Samsung Galaxy and Google Pixel devices. Support for Programmable Power Supply (PPS) allows the charger to dynamically adjust power output for improved charging efficiency and reduced heat during operation.

Built with GaN technology, the charger offers enhanced power efficiency in a more compact form factor, enabling higher performance with reduced heat generation compared to traditional chargers.

Built with comprehensive safety protection, the charger safeguards connected devices against overload, short circuits, and overheating. Combining performance, broad compatibility, and dependable protection, the 90W USB PD Charger is a powerful and reliable charging solution for modern USB-C devices.

## Additional Information

| | |
|---|---|
| Number of cartons per pallet. | 25 piece |
| Pallet Net Depth. | 1200 millimeter |
| Pallet Net Width. | 800 millimeter |
| Pallet Net Height. | 1627.4 millimeter |
| Cables included. | AC |
| Power Plug Type. | EU |
| Number of outputs. | 1 |
| Fast charging technology. | GaN, Power Delivery 3.0, Programmable Power Supply (PPS) |
| Programmable power supply (PPS) (YES/NO). | Yes |
| Port 1 Power Output. | 5.0V/3.0A, 9.0V/3.0A, 12.0V/3.0A, 15.0V/3.0A, 20.0V/4.5A (PD); 3.3–21.0V/4.3A (PPS) |
| Cable length. | 120 centimeter |
| Harmonized System (HS) code. | 8504408390 |
| Customs product code (TARIC). | 8504408390 |
| Sustainability Compliance. | No |
| Operating temperature (T-T) Max. | 35 celsius |
| Operating temperature (T-T) Min. | -20 celsius |
| Storage relative humidity (H-H) Max. | 90% |
| Storage relative humidity (H-H) Min. | 5% |
| Operating relative humidity (H-H) Max. | 90% |
| Operating relative humidity (H-H) Min. | 5% |
| Storage temperature (T-T) Max. | 80 celsius |
| Storage temperature (T-T) Min. | -20 celsius |
| Quantity per Pack. | 1 piece |
| Package Depth. | 225 millimeter |

| | |
|---|---|
| Package Height. | 138 millimeter |
| Package Width. | 55 millimeter |
| Product Gross Weight. | 515 gram |
| Color. | Black |
| EAN. | 4015867245095 |
| Model Number. | OZUL10BE |
| Dimensions (W x D x H). | 131.5 x 57.2 x 31 mm |
| Product Height. | 31 millimeter |
| Product Width. | 131.5 millimeter |
| Product Depth. | 57.2 millimeter |
| Product Net Weight. | 0.41 kilogram |
| Product weight (kg). | 0.41 |
| Maximum AC Input. | 240 volt |
| Minimum AC Input. | 100 volt |
| Input current. | 1.8 ampere |
| Maximum power. | 90 watt |
| Power Protection Features. | Over current, Over power, Short circuit |
| Power input. | AC 100-240V, 1.8A max, 50-60Hz |
| Approval and Compliance. | CE. ERP, RoHS |
| Operating humidity. | 5% RH ~ 90% RH |
| Operating temperature. | -20°C ~ 35°C |
| Storage humidity. | 5% RH ~ 95% RH |
| Storage temperature. | -20°C ~ 80°C |
| Package Contents. | OZUL10BE Power cable Multilingual quick installation guide |

