Philips Signage Solutions
Video Wall Display

46"
Direct LED Backlight
Full HD

SignageSolutions

BDL4676XL



Create the most stunning video walls

with this LED zero-bezel display

Create the most mesmerising video walls with our range of video wall models. With practically zero bezel and stunning full HD picture quality, you're sure to create the most memorable visual experience.

Optimised for public viewing
- Full HD LED technology for brilliant images
- Bezel-less design for stunning video walls

High picture and video quality
- Advanced Colour Calibration

Operational flexibility
- Smart insert in the back cover to place a small PC
- Smart Control Software Suite
- Portrait mode operability
- IR Pass-through
- Network Controllability: RJ45
- Designed for 24/7 operation
- DVI Daisy Chain
- Display Port for faster graphics support

PHILIPS

Highlights

Full HD LED technology
White LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content, which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of the LCD backlight, resulting in a super high contrast ratio. It also gives superior colour reproduction thanks to consistent brightness across the screen.

Bezel-less design
Create the most stunning video walls with zero bezel displays. Configurable in a formation of up to 15 x 10 displays, and with some of the narrowest mullions in the industry, you will hardly notice the gap between the pictures, giving you the most incredible and memorable visual experience.

Advanced Colour Calibration
Ensure a uniform colour across all displays installed in your network thanks to our advanced colour calibration tool. This tool will automatically adjust all displays in your signage application to ensure the ultimate in colour consistency to give your audience the most memorable visual experience.

Smart Insert
Professional PCs are part of most public signage installations. Quite often they increase the overall depth of the display and cause a lot of cable clutter. So we have designed this display with Smart insert in the back cover, which is ideal for the integration of a professional small form factor PC. On top of that, the cable management system offers a great solution to keep your cables neat and professional-looking.

Smart Control
Control and manage all of the signage displays on your network with this powerful software tool, which allows you to change the settings of your display centrally via an RJ45 or RS232 connection. Smart Control allows you to set the video input, modify the colour settings, set the display's ID when creating video walls and even diagnose each display's status, giving you all the power you need to manage your displays from one central location.

IR Pass-through
Control all displays in your signage network through one single remote control, via the primary display. Simple and convenient, this means you don't have to worry about other displays changing configuration settings when using your remote control unit.

Portrait mounting possible
This display can also be safely and reliably mounted in portrait position.

Designed for 24/7 operation
Because business never sleeps, our signage displays are designed for 24/7 use. Taking advantage of superior components to ensure a higher level of quality, you can count on this range of models for complete around-the-clock reliability.

Display Port
Enjoy crystal-clear images with the high-bandwidth graphics support of the Display Port. As well as transmitting full high-definition video, the Display Port will also transmit audio, thus, eliminating the need for extra cables.

DVI Daisy Chain
Create a digital video wall of up to 150 displays in a 15 x 10 configuration with a DVI daisy chain. Simply connect the DVI Out port to a DVI in of another display to create the most stunning video wall experience around.

RJ45
Simple management of your display is available thanks to the introduction of a LAN (RJ45) port. You can configure each display or find out the status of each device quickly and conveniently via an RJ45 connection.


















Video Wall Display
46" Direct LED Backlight, Full HD

BDL4676XL/00

Specifications

Picture/Display
- Diagonal screen size: 46 inch / 117 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080p @ 60 Hz
- Brightness: 450 cd/m²
- Contrast ratio (typical): 3500:1
- Response time (typical): 6.5 ms
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.53 x 0.53 mm
- Display colours: 1.07 billion
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, 3D MA deinterlacing, Dynamic contrast enhancement, Motion compens. deinterlacing, Progressive scan

Connectivity
- PC: VGA-in D-Sub 15HD, VGA-out D-Sub 15HD, DVI-D x 1, RS232 D-Sub9, RS232 D-sub9 output, 3.5 mm PC audio input x 1, RJ45
- AV input: HDMI x 1, Component (BNC) x 1, IR in, Audio (L/R) x 1
- Other connections: Display Port, DVI Out, USB, External loudspeaker connector, AC-out, IR out
- AV output: Audio (L/R) x 1

Dimensions
- Set dimensions (W x H x D): 1023.68 x 578.27 x 111.81 mm
- Bezel width (L/T, R/B): 3.2 mm, 1.8 mm
- Bezel width (A to A): 5 mm
- Product weight: 24 kg
- Smart Insert mount: 100 x 100 mm, 100 x 200 mm
- VESA Mount: 400 x 400 mm
- MTBF: 60,000 hrs

Power
- Consumption (Typical): 72 W
- Standby power consumption: <0.5 W
- Power supply: 90-264 VAC, 50/60 Hz

Operating conditions
- Temperature range (operation): 0 - 40 °C
- Relative humidity: 10-90 %

Supported Display Resolution
- Computer formats

Resolution	Refresh rate
640 x 480	60, 67, 72, 75 Hz
800 x 600	60, 72, 75 Hz
1024 x 768	60 Hz
1280 x 768	60 Hz
1280 x 800	60 Hz
1280 x 1024	60 Hz
1360 x 768	60 Hz
1366 x 768	60 Hz
1440 x 900	60 Hz
1600 x 1200	60 Hz
1920 x 1080	60 Hz
1920 x 1200	60 Hz

- Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576p	50 Hz
576i	50 Hz
720p	50, 60 Hz
1080i	50, 60 Hz
1080p	50, 60 Hz

Convenience
- Placement: Portrait, Landscape
- Signal Loop Through: DVI, RS232, VGA, IR Loop through
- Tiled Matrix: up to 15 x 10
- Picture in picture: PIP
- Keyboard control: Hidden, Lockable
- Packaging: Reusable box
- Network controllable: RS232, HDMI (One Wire), RJ45
- Remote control signal: Lockable
- Ease of installation: Smart Insert, AC Out, Carrying Handles
- Energy-saving functions: Smart Power
- Safety control functions: Heat Control, Temperature Sensor
- Picture performance: Advanced colour control
- Screen-saving functions: Pixel shift, Low bright
- OSD Languages: English, French, German, Italian, Spanish, Dutch, Polish, Turkish, Simplified Chinese, Russian

Sound
- Built-in speakers: 2 x 12 W

Accessories
- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, User manual on CD-ROM, Quick start guide

Miscellaneous
- On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Simplified Chinese, Italian
- Regulatory approvals: CE, FCC, Class B, UL/cUL, CCC, C-Tick, RoHS, GOST, CB, BSMI, EPEAT
- Warranty: 3-year warranty

Issue date 2014-12-15

Version: 5.0.1

12 NC: 8670 001 01209
EAN: 87 12581 68134 0

© 2014 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com