Product data sheet

Specifications



Discontinued - Service only

APC NetShelter CX, 38U, Soundproof Server Rack Enclosure, 100V to 120V, Dark Grey, 1950H x 750W x 1130D mm

AR4038X431

Discontinued on: 12 July 2023

End-of-service on: 12 July 2023

Overview

Presentation	Specialized enclosures with integrated cooling, noise dampening, and power distribution for server and network applications in office environments.
Lead time	Special Order - Call for Quoted Lead Times

Main

Product or Component Type	Rack enclosure
Main Input Voltage	115 V 120 V
Main Output Voltage	100 V 120 V
Input Connection Type	NEMA 5-15P
Output connection type	11 NEMA 5-15R
Number of rack unit	38U
Provided equipment	Casters Installation guide Key(s) Leveling feet Rack Power Distribution Unit (PDU) Side Panels

Physical

Height	76.77 in (195 cm)
Width	29.53 in (75 cm)
Depth	44.49 in (113 cm)
Net Weight	446.44 lb(US) (202.5 kg)
Color	Gray
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Maximum Mounting Depth	34.65 in (88.01 cm)
Minimum Mounting Depth	28.35 in (72.01 cm)
Rack Width	19"
Permanent permissible load	1716 lb(US) (778.36 kg) static

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Input

Input Frequency	50/60 Hz

Conformance

Product Certifications	TAA compliance
Standards	EIA-310D

Ordering and shipping details

GTIN	731304298274

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.65 in (215 cm)
Package 1 Width	47.24 in (120 cm)
Package 1 Length	31.50 in (80 cm)
Package 1 Weight	507.06 lb(US) (230 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	2 year (manufacturer's defect)

Recommended replacement(s)