Product data sheet

Specifications



Discontinued

MGE Galaxy 3500 Parallel Maintenance Bypass, up to 3 units 20-30kVA 208V Floormount

G35TSBPAR20K30F

Discontinued on: 05 July 2021

End-of-service on: 18 October 2023

Overview

Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Rated power in VA	90000 VA
Provided Equipment	Installation guide

Physical

Height	58.54 in (148.7 cm)
Width	13.82 in (35.1 cm)
Depth	32.95 in (83.7 cm)
Net Weight	317.66 lb(US) (144.09 kg)
Mounting Support	Floor
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	60 Hz

Conformance

Product Certifications	CSA
Standards	CSA C22.2 No. 107.1 UL 1778

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 %
Operating altitude	0...10000 ft

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	32…113 °F (0…45 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…30000 ft (0.00…9144.00 m)

Ordering and shipping details

GTIN	731304275718

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.50 in (166.37 cm)
Package 1 Width	43.50 in (110.49 cm)
Package 1 Length	28.50 in (72.39 cm)
Package 1 Weight	451.95 lb(US) (205 kg)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	1 year repair or replace

Recommended replacement(s)