Product data sheet

Specifications



APC Smart-UPS VT Parallel Maintenance Bypass, up to 3 units 10-15kVA 208V Floormount

SUVTSBPAR10K15F

Discontinued on: 22 October 2021

Discontinued - Service only

Overview

Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Rated power in VA	45000 VA
Output connector type	Hard Wire 4-wire (3PH + G) 1
Provided Equipment	Installation guide User Manual

Physical

Height	58.54 in (148.7 cm)
Width	13.86 in (35.2 cm)
Depth	32.95 in (83.7 cm)
Net Weight	317.47 lb(US) (144 kg)
Mounting Support	Floor
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	60 Hz

Conformance

Standards	UL 1778

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 %
Operating altitude	0...10000 ft

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…30000 ft (0.00…9144.00 m)

Ordering and shipping details

GTIN	731304275596

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.50 in (166.37 cm)
Package 1 Width	43.50 in (110.49 cm)
Package 1 Length	28.50 in (72.39 cm)
Package 1 Weight	392.42 lb(US) (178 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	1 year repair or replace

Recommended replacement(s)