SHARP
Be Original.

PN-V600A



- 60” (152CM) VIDEO WALL DISPLAY WITH 24/7 OPERATION
- 450CD/M2 AND UV2A LCD TECHNOLOGY WITH 4000:1 CONTRAST RATIO
- ONLY 6.5MM BEZEL BETWEEN ACTIVE AREAS (4.1MM / 2.4MM)
- SHARP PROPRIETARY UV2A TFT PANEL
- 50.000 HOURS LIFE TIME MAX.
- WEIGHT 41 KG
- 5 X 5 MULTI-SCREEN CAPABILITY (ENLARGEMENT) INTERNAL
- MODULE SLOT SYSTEM

The PN-V600A ultra thin bezel model is mainly designed for video wall applications. This 152 cm (60") LCD-monitor with an enhanced contrast ratio can be used in a variety of signage and multi screen configurations. As a flexible solution with an almost seamless bezel, the PN-V600A sets a new standard for video wall displays.

DISPLAY MODULE DATA

- Panel Technology: **TFT-LCD**
- Native Resolution (Pixels): **1366 x 768**
- Diagonal Size (inches / cm): **60/152,4**
- Aspect Ratio: **16:9**
- Backlight Technology: **LED. Direct array**
- Brightness (cd/m2): **450**
- Contrast Ratio: **4000:1**
- Display Colours: **16,7 million**
- Response Time (grey to grey avg) ms: **6**
- Viewing Angle (H/V)0 CR >10: **176/176**

POWER SUPPLY AND OPERATING ENVIRONMENT

- Operating Voltage(ACV) / Frequency(Hz): **100-240/50-60**
- Power Consumption (W) (Operating MAX): **310**
- Power Consumption (W) (Standby): **1**
- Operating Temperature (oC): **0-40**
- Humidity (%): **20-80**

WEIGHTS AND MEASURES

- Bezel Size (L/R) mm: **4,1/2,4**
- Bezel Size (U/L) mm: **4,1/2,4**
- Video Wall Bezel (Content to Content) mm: **6,5**
- Product Dimensions (W/H/D) mm: **1,335.9 x 754.2 x 149.3**
- Product Weight Without Stand (Kg): **41**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- HDMI: **1**
- DVI-D: **1 (OPT PN-ZB02)**
- VGA: **1**
- Component: **1 (OPT PN-ZB02)**
- Composite: **1 (OPT PN-ZB02)**
- S-Video: **1 (OPT PN-ZB02)**
- Audio 3.5mm Jack: **1**
- Audio RCA R-L: **2 (OPT PN-ZB02)**

CONNECTIVITY (CONTROL/SERIAL DATA)

- RS232C IN: **1**
- RS232C OUT: **1**
- LAN Port: **1 (OPT PN-ZB02)**

KEY SPECIFICATIONS

- 24/7 Operation Certified: ✓
- Computer Input - Plug and Play: ✓
- Power Management: ✓
- Brightness Sensor: ✓
- Multi-Screen Function - Videowall Mode (Enlarge Feature): ✓
- Bezel Correction Feature: ✓
- Remote Management: ✓
- Daisychain (Mirror mode): ✓
- Hardware Diagnosis: ✓
- Monitor Control Software Support: ✓

SAFETY AND ENVIRONMENT (EUROPE)

- CE, CB Report: ✓

INSTALLATION

- Landscape: ✓
- Portrait: ✓
- Horizontal: ✓
- Mounting (VESA/Number of Points/Pitch mm): **6/200mm x 200mm or 4/ 200mm x 200mm**

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- DVI-D: **1 (OPT PN-ZB02)**
- Audio RCA R-L: **1**
- External Speaker: **10W + 10W (OPT PN-ZB02)**

www.sharp.co.uk

SHARP
Be Original.

SHARP BUSINESS SYSTEMS UK PLC.
4 FURZEGROUND WAY
STOCKLEY PARK
UXBRIDGE, MIDDLESEX UB11 1EZ. TEL. 0208 734 2000