Specifications



Eaton EMI309-10

Eaton Metered Input rack PDU, 0U, L21-20P input, 5.76 kW max, 120/208V, 16A, 10 ft cord, Three-phase, Outlets: (39) 5-20R

General specifications	
PRODUCT NAME	Eaton metered input PDU
CATALOG NUMBER	EMI309-10
PRODUCT LENGTH/DEPTH	2.05 in
PRODUCT HEIGHT	66.5 in
PRODUCT WIDTH	2.1 in
PRODUCT WEIGHT	15.15 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Metered input PDU

Powering Business Worldwide

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	No
PHASE	Three-phase
WATTAGE	5.76 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	120/208V
INPUT CONNECTION	L21-20P
OUTLETS	(39) 5-20R
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU G3 Metered Input EMI309-10 technical drawing
MANUALS AND USER GUIDES	Eaton ePDU G3 instruction set - system objects Eaton ePDU G3 EMP installation and connection quick start guide Eaton ePDU G3 operations manual Eaton ePDU G3 installation and connectivity quick start guide
SERVICE AND TROUBLESHOOTING	EMI309-10 eNMC replacement configuration file
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMI309-10

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.