

MASTER PL-S 4 Pin

MASTER PL-S 7W/840/4P 1CT/5X10BOX

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 2 parallel narrow fluorescent tubes

Product data

• General Information

Cap base	2G7 [2G7]
Life to 50% failures preheat (nom.)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	92 %
LSF Preheat 16000 h Rated	30 %

• Light Technical

Luminous flux (nom.)	400 lm
Luminous flux (rated) (nom.)	405 lm
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	381
Chromaticity coordinate Y (nom.)	379
Correlated colour temperature (nom.)	4100 K
Luminous efficacy (rated) (nom.)	62 lm/W
Color rendering index (nom.)	82
LLMF 2000 h Rated	95 %
LLMF 4000 h Rated	92 %
LLMF 6000 h Rated	90 %
LLMF 8000 h Rated	88 %
LLMF 12000 h Rated	86 %

• Operating and Electrical

Power (Rated) (Nom)	7.1 W
Lamp current (nom.)	0.175 A

• Temperature

Design temperature (nom.)	28 °C

• Controls and Dimming

Dimmable	yes

• Mechanical and Housing

Cap base information	4P

• Approval and Application

Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	8 kWh

• Product Data

Full product code	871150026076570
Order product name	MASTER PL-S 7W/840/4P 1CT/ 5X10BOX
EAN/UPC – product	8711500260765
Order code	26076570
Local Code	7PLS8404PINB

PHILIPS

MASTER PL-S 4 Pin


Numerator – quantity per pack	1
Numerator – packs per outer box	50

Material no. (12NC)	927935884011
Net weight (piece)	24.000 g
ILCOS Code	FSD-7/40/1B-E-2G7


Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




2G7, 4P



PL-S 7W/840/4P LM

Product	D	D1	A	B	C
MASTER PL-S 7W/840/4P 1CT/5X10BOX	28 mm	13 mm	96 mm	113 mm	119.1 mm

Photometric data



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 28
data subject to change