

MASTER TL5 High Output

MASTER TL5 HO 49W/840 1SL/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Product data

• General Information

Cap base	G5 [G5]
Bulb shape	T5 [16 mm (T5)]
Life to 50% failures preheat (nom.)	30000 h
Features	na [Not Applicalbe]
System description	High Output (HO)
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	97 %
LSF Preheat 20000 h Rated	84 %

• Light Technical

Luminous flux (nom.)	4900 lm
Luminous flux (rated) (nom.)	4375 lm
Colour designation	Cool White (CW)
Luminous efficacy (@ max. lumen, rated) (nom.)	99 lm/W
Chromaticity coordinate X (nom.)	380
Chromaticity coordinate Y (nom.)	380
Correlated colour temperature (nom.)	4100 K
Luminous efficacy (rated) (nom.)	89 lm/W
Color rendering index (max.)	85
Color rendering index (min.)	80
Color rendering index (nom.)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	90 %
LLMF 20000 h Rated	90 %

• Operating and Electrical

Power (Rated) (Nom)	49.2 W
Lamp current (nom.)	0.255 A

• Temperature

Design temperature (nom.)	35 °C

• Controls and Dimming

Dimmable	yes

• Mechanical and Housing

Cap base information	Green Plate

• Approval and Application

Energy efficiency label (EEL)	A+

PHILIPS

MASTER TL5 High Output

Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	54 kWh

- Product Data

Full product code	871150063956155
Order product name	MASTER TL5 HO 49W/840 SLV/40
EAN/UPC – product	8711500639561
Order code	63956155
Local Code	49840
Numerator – quantity per pack	1
Numerator – packs per outer box	40
Material no. (12NC)	927927584055
Net weight (piece)	128.700 g
ILCOS Code	FDH-49/40/1B-L/P-G5-16/1450

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing

TL5 HO 49W/840

Product	D	A	B	B	C
MASTER TL5 HO 49W/840 SLV/40	1456.1 mm	1453.7 mm	1463.2 mm		



G5, T5



Photometric data







© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, October 10
data subject to change