PHILIPS

Lighting



MASTER TL-D Reflex

MASTER TL-D Reflex 58W/865 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Product data

General Information	
Cap base	G13 [Medium Bi-Pin Fluorescent]
Life to 10% failures (nom.)	12000 h
Life to 50% failures (nom.)	15000 h
Life to 50% failures preheat (nom.)	20000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	89 %
LSF 16000 h Rated	33 %
LSF 20000 h Rated	2 %

Light Technical	
Colour code	865 [CCT of 6500K]
Luminous flux (nom.)	5000 lm
Luminous flux (rated) (nom.)	5000 lm
Beam description	FA160 [160° Window]
Colour designation	Cool Daylight
Chromaticity coordinate X (nom.)	312
Chromaticity coordinate Y (nom.)	330
Correlated colour temperature (nom.)	6500 K
Luminous efficacy (rated) (nom.)	85.5 lm/W
Color rendering index (nom.)	85
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

Operating and Electrical	
Power (Rated) (Nom)	58.5 W
Lamp current (nom.)	0.670 A

Temperature	
Design temperature (nom.)	25 °C

Controls and Dimming	
Dimmable	yes

Mechanical and Housing	
Bulb finish	Reflector
Cap base information	na [-]

Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	5.0 mg

MASTER TL-D Reflex

Energy Consumption kWh/1000 h	68 kWh

Numerator – quantity per pack	1
Numerator – packs per outer box	25
Material no. (12NC)	928048986579
Net weight (piece)	167.000 g
ILCOS Code	FDR-58/65/1B-E-G13


Product Data

Full product code	871150026033840
Order product name	MST TL-D Reflex 58W/865 1 SLV/25
EAN/UPC – product	8711500260338
Order code	26033840
Local Code	58865RFECO

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MST TL-D Reflex 58W/865 1 SLV/25	28 mm	1500.0 mm	1507.1 mm	1504.7 mm	1514.2 mm

TL-D Reflex 58W/865

Photometric data



Lightcolour /865



Lightcolour /865



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com
2017, May 26 - data subject to change