

MSR Hot Restrike

MSR 575 HR 1CT/4

High-efficiency hot restrike metal halide lamps designed for optimum light collection

Product data

General Information	
Cap base	G22 [G22]
Operating position	UNIVERSAL [Any/Universal]
Main application	Studio/Theatre
Life to 50% failures (nom.)	1000 h
System description	Hot Restrike

Light Technical	
Colour code	- [Not Specified]
Luminous flux (min.)	40000 lm
Luminous flux (nom.)	49000 lm
Chromaticity coordinate X (nom.)	323
Chromaticity coordinate Y (nom.)	328
Correlated colour temperature (nom.)	6000 K
Luminous efficacy (rated) (nom.)	85 lm/W
Color rendering index (nom.)	90

Operating and Electrical	
Power (Rated) (Nom)	575 W
Lamp current (nom.)	6.95 A
Ignition supply voltage (min.)	207 V

Controls and Dimming	
Dimmable	yes

Mechanical and Housing	
Cap base information	na [-]

Luminaire Design Requirements	
Bulb temperature (max.)	700 °C
Pinch temperature (max.)	350 °C


Product Data	
Full product code	871829122105000
Order product name	MSR 575 HR 1CT/4
EAN/UPC – product	8718291221050
Order code	22105000
Local Code	MSR575HR
Numerator – quantity per pack	1
Numerator – packs per outer box	4
Material no. (12NC)	928097705115
Net weight (piece)	0.100 kg

MSR Hot Restrike

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




MSR 575 HR

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 575 HR 1CT/4	30 mm	7.0 mm	69 mm	71 mm	70 mm	145 mm	43 mm	42 mm	41 mm

Photometric data





© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.