Product specifications

Eaton EMO115-10

Catalog Number: EMO115-10

Eaton Metered Outlet Rack PDU, 0U, C20 input, 3.84 kW max, 100-240V, 16A, 10 ft cord, Single-phase, Outlets: (21) C13 Outlet grip, (3) C19 Outlet grip



General specifications

Product Name	**Catalog Number**
Eaton Metered Outlet Rack PDU	EMO115-10
UPC	**Product Length/Depth**
743172079237	63.1 in
Product Height	**Product Width**
2.05 in	2.09 in
Product Weight	**Warranty**
6.9 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

ePDU

Form factor

0U (Vertical)

Outlet control

No

Operating Temperature

0° to 60°C (32° to 140°F)

Mounting direction

Vertical

Color

Black

Input connection

C20

Cord length

10 ft

Wattage

3.84 kW max

Amperage Rating

16A

Input voltage

100-240V

Phase

Single-phase

Frequency rating

50-60 Hz

Outlets

(21) C13 Outlet grip, (3) C19 Outlet grip

Circuit breaker

None

Ethernet interface

Yes

Serial interface

RS-232

Switchable

Resources

Drawings

Eaton ePDU G3 Metered Outlet visio stencils

Eaton ePDU G3 Metered Outlet EMO115-10 technical drawing

Manuals and user guides

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

Service and troubleshooting

EMO115-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMO115-10

No

Fitted with:

Ampere Meter

Series

Metered Outlet

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia