# REDUNDANT

## MRT-5320G // SLEEVED// 320WATT



| | |
|---|---|
| **Product:** | PSU |
| **Form factor:** | PSII |
| **Color:** | silver |

If you are looking for "green-power" and high-performance 24-7, then the MRT-5320G will be the choice.

**Certificates:**

## Technical data

| | |
|---|---|
| **Specification:** | ATX 12V 2.3 |
| **Efficency:** | >90% |
| **Dimensions (DxWxH):** | 185mm x 150 mm x 87 mm |
| **PCF:** | Active PFC (0,9) |
| **Fan:** | 40mm fan (2x 40mm per module) |

**Connectors**

| 24 PIN | 8PIN EPS | System LED | SATA | Molex | Floppy | TTL Signal Kabel | Buzzer |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 2 | 5 | 1 | 1 | 1 |

| 8PIN EPS (4+4) | 6PIN PCIe | 8 PIN PCIe (6+2) |
|---|---|---|
| 1 | 0 | 0 |

**DC Output / AC Input**

| AC INPUT: 100V / 5A 240V / 3A<br>FREQUENCY: 47 - 63 HZ<br>MAX. LOAD: 320W | DC OUTPUT | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | +5V | +3,3V | +12V1 | +12V2 | +12V3 | -5V | P.F. | -12V | +5VSB |
| | 25A | 25A | 26A | N/A | N/A | N/A | >0,9 | 0,5A | 3,0A |
| | 150W | | N/A | | | | | | |

| | |
|---|---|
| **Security:** | Met.al frame, 2x 320W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC |

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.

Arena Electronic GmbH
Koppersstr. 18
DE-40549 Düsseldorf

www.chieftec.eu

Tel. +49 (0) 211 91 31 51 - 0
Fax. +49 (0) 211 91 31 51 – 99
Email: info@chieftec.eu