Product specifications

Eaton EMI121-10



Catalog Number: EMI121-10

Eaton Metered Input rack PDU, 0U, L6-30P input, 10 ft cord, 200-240V, 5.76 kW max, Single-phase, Outlets: (12) C13 Outlet grip, (2) C19 Outlet grip

General specifications

Product Name	**Catalog Number**
Eaton metered input rack PDU	EMI121-10
UPC	**Product Length/Depth**
786685955322	35.5 in
Product Height	**Product Width**
2.09 in	2.05 in
Product Weight	**Warranty**
6.6 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Single-phase

Wattage
5.76 kW max

Amperage Rating
24A

Input voltage
200-240V

Input connection
L6-30P

Outlets
(12) C13 Outlet grip, (2) C19 Outlet grip

Cord length
10 ft

Frequency rating
50-60 Hz

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI121-10 technical drawing

Eaton PDU EMI121-10 technical drawing

Manuals and user guides
Eaton ePDU G3 operations manual

Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 EMP installation and connection quick start guide

Eaton ePDU G3 instruction set - system objects

Service and troubleshooting
EMI121-10 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI121-10

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia