Product specifications

Eaton EMI363-06



Catalog Number: EMI363-06

Eaton Metered Input rack PDU, 0U, CS8365 input, 14.4 kW max, 200-240V, 40A, 6 ft cord, Three-phase, Outlets: (38) C13

General specifications

Product Name	**Catalog Number**
Eaton metered input rack PDU	EMI363-06
UPC	**Product Length/Depth**
786685974538	69.5 in
Product Height	**Product Width**
2.1 in	2.05 in
Product Weight	**Warranty**
18 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

Product specifications

Form factor
0U (Vertical)

Outlet control
No

Phase
Three-phase

Wattage
14.4 kW max

Amperage Rating
40A

Input voltage
200-240V

Input connection
CS8365

Outlets
(38) C13

Cord length
6 ft

Frequency rating
50-60 Hz

Ethernet interface
Yes

Serial interface
RS-232

Operating Temperature
0° to 60°C (32° to 140°F)

Resources

Certification reports
Eaton RoHS Declaration of Conformity: ePDU G3

Drawings
Eaton ePDU G3 Metered Input EMI363-06 technical drawing

Eaton PDU EMI363-06 technical drawing

Manuals and user guides
Eaton ePDU G3 installation and connectivity quick start guide

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

Eaton ePDU G3 EMP installation and connection quick start guide

Service and troubleshooting
EMI363-06 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMI363-06



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia