Product specifications

Eaton EMO329-06



Catalog Number: EMO329-06

Eaton Metered Outlet Rack PDU, 0U, CS8365 input, 14.4 kW max, 200-240V, 40A, 6 ft cord, Three-phase, Outlets: (12) C13 Outlet grip, (12) C19 Outlet grip

General specifications

Product Name	**Catalog Number**
Eaton Metered Outlet Rack PDU	EMO329-06
UPC	**Product Length/Depth**
743172079732	66.5 in
Product Height	**Product Width**
2.05 in	2.56 in
Product Weight	**Warranty**
18.6 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type
ePDU

Form factor
0U (Vertical)

Outlet control
No

Operating Temperature
0° to 60°C (32° to 140°F)

Mounting direction
Vertical

Color
Black

Input connection
CS8365

Cord length
6 ft

Wattage
14.4 kW max

Amperage Rating
40A

Input voltage
200-240V

Phase
Three-phase

Frequency rating
50-60 Hz

Outlets
(12) C13 Outlet grip, (12) C19 Outlet grip

Circuit breaker
(6) 20A

Ethernet interface
Yes

Serial interface
RS-232

Switchable

Resources

Drawings
Eaton ePDU G3 Metered Outlet EMO329-06 technical drawing

Eaton ePDU G3 Metered Outlet visio stencils

Manuals and user guides
Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 operations manual

Service and troubleshooting
EMO329-06 eNMC replacement configuration file

Specifications and datasheets
Eaton Specification Sheet - EMO329-06

No

Fitted with:

Ampere Meter

Series

Metered Outlet

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia