

Halogen non-reflector

6550 150W G6.35 15V 1CT/10X10F

Low-voltage quartz halogen capsule lamps

Product data

• General Information

Cap base	G6.35 [G6.35]
Philips code	6550
ANSI Code	EVB-BRJ
Operating position	S90 [Standing +/-90D or Base Down (BDH)]
Main application	Projection
Life to 50% failures (nom.)	50 h

• Light Technical

Luminous flux (rated) (nom.)	5600 lm
Correlated colour temperature (nom.)	3450 K
Color rendering index (nom.)	100

• Operating and Electrical

Power (Rated) (Nom)	150 W
Voltage (Nom)	15 V

• Mechanical and Housing

Bulb material	Quartz-UV Open
Filament shape	Flat
Filament dimensions WxH	4.8x3.0

• Luminaire Design Requirements

Bulb temperature (max.)	900 °C
Pinch temperature (max.)	400 °C


• Product Data

Full product code	871150040984350
Order product name	6550 150W G6.35 15V 1CT/10X10F
EAN/UPC – product	8711500409843
Order code	40984350
Local Code	A1234
Numerator – quantity per pack	1
Numerator – packs per outer box	100
Material no. (12NC)	923870618503
Net weight (piece)	0.002 kg

PHILIPS

Halogen non-reflector


Dimensional drawing




G6.35, GY6.35

6550 150W G6.35 15V

Product	D	L	L	L	P	P	P	C (max)
6550 150W G6.35 15V 1CT/10X10F	11.5 mm	29.75 mm	30.25 mm	30 mm	1.05 mm	1 mm	0.95 mm	





© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, October 11
data subject to change