ThinkCentre M600 Tiny Platform Specifications

Processor

Intel® Celeron® Processor N3000 Series or Intel Pentium® Processor N3000 Series

Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Integrated Graphics
Celeron N3000	2 / 2	1.04 / 2.08 GHz	2MB	DDR3L-1600	Intel HD
Celeron N3010	2 / 2	1.04 / 2.24 GHz	2MB	DDR3L-1600	Intel HD 400
Celeron N3050	2 / 2	1.6 / 2.16 GHz	2MB	DDR3L-1600	Intel HD
Pentium N3700	4 / 4	1.6 / 2.4 GHz	2MB	DDR3L-1600	Intel HD
Pentium J3710	4 / 4	1.6 / 2.64 GHz	2MB	DDR3L-1600	Intel HD 405

Chipset

Intel Architecture (IA) SoC that integrates Intel processor core, graphics, memory controller, and I/O interfaces into a single system-on-chip solution

Graphics

Intel HD Graphics in processor, uses main memory, DirectX® 11.1, twoDisplayPort™, one optional 3rd DP or VGA, supports triple independent display; Maximum resolution: 3840x2160(DP)@30Hz; 1920x1200(optional VGA)@60Hz; 1920x1080(DP to VGA dongle)@60Hz; 1920x1080(DP to DVI dongle)@60Hz; 3840x2160(DP to HDMI dongle)@30Hz

Monitor cable

Optional DP to VGA, DP to DVI-D (single link), or DP to HDMI 1.4 dongle

Memory

8GB max / DDR3 Low Voltage, DDR3L-1600, non-parity, one 204-pin SO-DIMM socket

Storage

Some: M.2 Solid State Drive (SSD), SATA interface
Some: hard disk, 5400 or 7200 rpm, SATA 6.0Gb/s, 2.5" Wide
Some: 500GB (5400 rpm) Solid State Hybrid Drive (SSHD) / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide
Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide

Optical

Some: external ODD box with DVD-ROM, 9.5mm high, via USB
Some: external ODD box with DVD±RW, 9.5mm high, via USB
Some: external ODD box (for TIO) with DVD-ROM, 9.5mm high, via USB
Some: external ODD box (for TIO) with DVD±RW, 9.5mm high, via USB

Onboard SATA

SATA 6.0Gb/s controller, one connectors on planar

Media reader

None

Front ports

Two USB 3.0 (one is Always On and fast charge), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)

Rear ports

Two USB 2.0, two USB 3.0 (optional external optical box or I/O box occupies one or two specific USB on some models), ethernet (RJ-45), two DisplayPort, one optional port (VGA, 3rd DP, or serial on some models), one headphone; additional four serial (9-pin), one parallel (25-pin), and two PS/2 ports on 2L models

I/O box

Optional external I/O box, extends two USB 2.0, two USB 3.0, and one serial on rear, two USB 2.0 on front, via USB (occupy two specific USB 3.0 of M600 Tiny)

Audio support

High Definition (HD) Audio, Realtek ALC223 / optional internal speaker (1 watt)

WLAN[13]

Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 1x1
Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1
Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2
Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1
Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8260, Wi-Fi + Bluetooth 4.1 combo adapter, 2x2

Bluetooth™

Some: Bluetooth 4.0 or 4.1 wireless, integrated in Wi-Fi + BT combo adapter

Ethernet

One gigabit ethernet port, Realtek RTL8111GN, Wake on LAN®

Modem

None

Manageability

None

Security chip

Trusted Platform Module, TCG 1.2-compliant

Security features

- Security slot (in rear for optional Kensington® MicroSaver® cable)
- Padlock loop
- Smart USB protection, allows keyboard/mouse only, blocks all storage devices
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement
- Chassis intrusion switch

Keyboard

Some: PS/2 Keyboard (PS/2 connector), Lenovo logo
Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo
Some: Lenovo USB Fingerprint Keyboard (USB connector)
Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black

Mouse

Some: PS/2 Optical Wheel Mouse, black, Lenovo logo
Some: Enhanced Optical USB Mouse, black, Lenovo logo
Some: Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black

Mechanical

- Tiny (1L or 2L), black color; metal case

	Dimensions (WxDxH)	Max weight (lb / kg)
M600 Tiny only (1L)	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.9 lb (1.3 kg)
M600 Tiny only (2L)	7.05" X 7.20" X 3.15" 179mm X 182.9mm X 80mm	4.2 lb (1.9 kg)
M600 Tiny (1L) with VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	4.12 lb (1.87 kg)
M600 Tiny (1L) with VESA mount & I/O box	7.42" X 7.30" X 2.62" 188.4mm X 185.38mm X 66.6mm	3.53 lb (1.6 kg)

VESA mount

Optional VESA mount bracket kit, supports VESA 75mm and 100mm

Floor Stand

Optional system floor stand for vertical orientation

Power supply

65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models)
90 watts AC/DC adapter, autosensing, 88% PSU (only for models with I/O box)

Limited warranty[3]

Some: 1-year or 3-year, depot service / service upgrades available
Some: 1-year or 3-year, limited onsite service / service upgrades available
Some: 3-year, limited onsite service, OID (Onsite International Delivery) / service upgrades available
For Lenovo service upgrade options, please go to S-TC sheet

Preload

Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 10 Pro 64-bit
Some: Windows 7 Professional 64
Some: Windows® 10 Pro 64-bit
Some: Windows 10 Home 64-bit
Some: Windows® Embedded Standard 7 (WES 7)
Some: LeTOS (Lenovo Terminal Operating System, Linux-based)

Preloaded applications (only some listed)

- Desktop Power Manager
- Lenovo Solution Center
- Lenovo REACHit
- Lenovo SHAREit
- Lenovo Bluetooth Lock
- McAfee® LiveSafe™ (30-day trial)
- Microsoft Office preloaded; purchase a product key to activate
- PowerDVD Create (DVD±RW)
- Lenovo ThinkVantage Tools

- Only for Window 10

- Lenovo Companion (Win10)
- Cyberlink PowerDVD (DVD, DVD±RW)
- Lenovo QuickOptimizer

- Only for Window 7

- Rescue and Recovery
- Password Manager
- ThinkVantage System Update
- Lenovo Message Center Plus
- Adobe® Reader®

Preloaded applications (only some listed)

- WES 7 only:
- RDP Client (RDP 8.1 support)
- Citrix Client
- VMware Client
- Internet Explorer 11
- Java
- Flash
- .Net Framework
- Microsoft® Silverlight
- Echo Agent (client for LTM, Lenovo Thin Client Manager)
- Adobe Reader
- UltraVNC

- LeTOS only:

- xFreeRDP
- Citrix ICA Client
- VMware View Client
- Java
- Mozilla Firefox

Environment

ENERGY STAR® 6.0*, EPEAT™ Gold rating* (*for Windows models only); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3

Accessories

For compatible accessories, please go to TC-AQP sheet

See footnotes for more detailed information

© Lenovo

Model	10G9001A++
Product	ThinkCentre M600 Tiny
Region	WE
Machine Type	10G9
TopSeller	TopSeller
Case 1L/2L	1L
Processor	Pentium J3710 (4C, 1.60 / 2.64GHz, 2MB)
vPro	No
Graphics	Integrated Intel HD Graphics 405
Monitor Cable	None
Memory	4GBx1
Storage	500GB 5400rpm 2.5"
External Optical / I/O Box	None
WLAN + Bluetooth	QCA9377 ac, 1x1 + BT4.1
Optional Rear Ports	None
Chassis Intrusion Switch	Chassis Intrusion Switch
Kensington Cable Lock	None
Speaker	1Wx1
Adapter Cage	None
Toolless Chassis Screw	None
Keyboard / Mouse	USB / USB
VESA Mount	VESA Mount
Stand	None
Power Supply	65W Adapter 88%
Operating System	Windows 10 Pro 64
Warranty	3-year, Onsite
Global	No
Ann Date (mm/yy)	07/16


Lenovo


Lenovo
ThinkCentre




ThinkCentre
Lenovo




Lenovo






Lenovo




Lenovo
ThinkCentre


COM 3
COM 4
COM 2
COM 1