Product specifications

Eaton EMI357-10

Catalog Number: EMI357-10

Eaton fuse disconnect rack PDU, 0U, L22-30P input, 17.3 kW max, 230/400V, 24A, 10 ft cord, Three-phase, Outlets: (48) C13 Outlet grip, (12) C19 Outlet grip



General specifications

Product Name	**Catalog Number**
Eaton fuse disconnect rack PDU	EMI357-10
UPC	**Product Length/Depth**
786685991450	63.2 in
Product Height	**Product Width**
2.09 in	4.1 in
Product Weight	**Warranty**
15.8 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

Physical

Mounting direction

Vertical

Color

Black

Form factor

0U (Vertical)

Electrical input

Input connection

L22-30P

Cord length

10 ft

Wattage

17.3 kW max

Amperage Rating

24A

Input voltage

230/400V

Phase

Three-phase

Frequency rating

50-60 Hz

Electrical output

Outlets

(48) C13 Outlet grip, (12) C19 Outlet grip

Circuit breaker

(6) 20A Fuse

Outlet control

No

Communications

Ethernet interface

Yes

Serial interface

RS-232

Additional specifications

Switchable

No

Operating Temperature

0° to 60°C (32° to 140°F)

Series

Metered Input

Resources

Certification reports

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings

Eaton ePDU G3 Metered Input EMI357-10 technical drawing

Eaton Fuse Disconnect EMI357-10 technical drawing

Manuals and user guides

Eaton ePDU G3 operations manual

Eaton ePDU G3 instruction set - system objects

Service and troubleshooting

EMI357-10 eNMC replacement configuration file

Specifications and datasheets

Eaton Specification Sheet - EMI357-10

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia