CAT. N° 3 109 60



ADDITIONAL BATTERY CHARGER - FOR BATTERY CABINET CAT.NO 3 105 99

Pack (number of units)	1
Volume (dm³)	11,977
Weight (g)	2 465,00

Product characteristics

Additional battery cabinets

Additional battery chargers

- For battery cabinet Cat.No 3 105 99

General characteristics

Keor LP - On-line double conversion UPS (tower) - single phase VFI

- For security systems, lighting systems, CCTV, servers. Ideal for environments with frequent electrical disturbances
- Installation: downstream power generators. Advanced management depending on the battery discharge level
- Self-diagnosis. Power factor: 0.9
- Automatic internal bypass, manual bypass for external maintenance (optional)
- Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
- Cold Start function
- Microprocessor control
- Telephone line/Internet protection (RJ 11/RJ 45)
- Internal network interface Cat.No 3 108 82 for remote protection of equipment and systems
- Remote emergency shutdown function ("Emergency Power Off" - EPO)

Documentation

Catalogue pages & additional information

- Description page (p.704)

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.