Classic Globe (GLS) 13.5W (100W) 2700K 1521lm E27 Dimmable Frosted Lamp



This 13.5W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a dimmable, warm light and brightness. With a 1521 lumen output, this lamp is one of only a few true 100W filament bulb replacements available today. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

Product Details

Partcode: ILA60E27O14D27KBKMA

Check Code: 114268

Range Name: Mensae

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: GLS

Warranty: 2 Years

CE / RoHS: Yes

Physical Data

Lamp Base: E27

Base Type: Edison screw

Base Colour: Matt white

Globe Type: Classic Globe (GLS)

Globe Finish: Frosted

Material: Aluminium, Polycarbonate

Construction: Aluminium and Plastic heat-sink, Injection moulded diffuser

Product design and specification subject to change or modification without notice. Image for illustration only. E&OE

Physical Data

Length: 122mm

Width: 60mm

Weight (Unpackaged Single Unit): 121g

Lamp or Luminaire Shape: Round

Lamp Fixing: Pendant, Wall

Electrical Data

Voltage Range: 220-240V

Power Consumption: 13.5 Watts

Driver included: Yes

Driver IC Manufacturer: Marvel

Electric Current: AC

Ampage: 70.00mA

Frequency Range: 50 Hz

Power Factor: >=0.90

Wattage Equivalent: 100 Watts

Dimming: Dimmable with compatible dimmers

Compatible Dimmer(s): Varilight JQP401W

LVD Certified: Yes

EN: EN-62560

Light Data

Lumens: 1,521lm

Lumens per Watt: 113.0lm/W

Beam Angle: 200º

Correlated Colour Temperature (CCT): 2,700k

Colour Temperature: Warm

Colour Rendering Index (CRI): >=80

LED Type: Surface mounted device (SMD)


Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs

Switching Cycles: >7,500 X

Product design and specification subject to change or modification without notice. Image for illustration only. E&OE

Environmental



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788212591

Packaged Weight (Unit of 1): 160g

Length (unit of 1): 135mm

Width (unit of 1): 68mm

Depth (unit of 1): 68mm

Outer packaging info available on website

Product data last updated on: Friday, September 29, 2017 - 17:32

Product design and specification subject to change or modification without notice. Image for illustration only. E&OE