Data Sheet
FUJITSU Tablet STYLISTIC R727

Unlimited Usability and Productivity with 2 in 1

The FUJITSU Tablet STYLISTIC R727 with a 31.8 cm (12.5-inch) anti-glare display transforms into a full performance and full productivity notebook by simply attaching the strong yet slim magnetic keyboard. Its magnesium-aluminum housing delivers durability for business pros on the move, presenting in tablet mode or working in notebook mode anywhere you like. With the sensitive display you can naturally use a digital pen for notes or signatures on the tablet. Enterprise-grade connectivity like 4G/LTE, manageability and security features like encrypted drives and NFC-based authentication allow you to do your job wherever you want; all in confidence that your data is secure.



Powerful and responsive 2 in 1
Business tablet, business notebook, one device
- Transform a tablet into a full-fledged notebook by simply attaching the magnetic keyboard and unfolding the integrated tablet stand



Mobility first
Smart features for dynamic work styles
- Anti-glare display, durable yet thin & light magnesium-aluminum housing, flexible input options, UC&C capabilities, long runtime of up to 10 hours

Go-anywhere connectivity
Smart features let you do your job wherever you want
- Optional embedded 4G/LTE and NFC

Enterprise-grade manageability and security
Future-proof security features and remote management capabilities keep data safe
- Embedded NFC for contactless SmartCard authentication, encrypted drives, TPM and remote BIOS manageability



Best-in-class office comfort
Switch to a full desktop-like experience in no time
- Cradle to attach peripherals in the office

Components

Operating systems				
Operating system	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Microsoft OS support information	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.
	*Processor only for retail, SMB, education and government			
Hard disk drives (internal)	SSD SATA III, 512 GB, M.2 module, OPAL capable			
	SSD SATA III, 256 GB, M.2 module, OPAL capable			
	SSD SATA III, 128 GB, M.2 module, OPAL capable			
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: M.2 SATA			
Interface add on cards/components (optional)				
Multimedia				
Camera	Front camera 2 megapixel, rear camera 5 megapixel with autofocus			

Base unit

General system information				
Processor	Intel® Core™ i3-7100U processor (2 Cores / 4 Threads, up to 2.3 GHz)	Intel® Core™ i5-7200U processor (2 Cores / 4 Threads, up to 2.8 GHz)	Intel® Core™ i5-7300U processor (2 Cores / 4 Threads, up to 3.0 GHz)	Intel® Core™ i7-7600U processor (2 Cores / 4 Threads, up to 3.4 GHz)
Chipset	Integrated in CPU	Integrated in CPU	Integrated in CPU	Integrated in CPU
Supported capacity RAM	4 GB	8 GB	8 GB	16 GB
Memory slots	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)
LAN	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219LM	Built-in 10/100/1,000 MBit/s Intel® I219LM
LAN notes	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable
Integrated WLAN	Intel Dual Band Wireless-AC8265	Intel Dual Band Wireless-AC8265	Intel Dual Band Wireless-AC8265	Intel Dual Band Wireless-AC8265
BIOS features	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board	On board	On board

General system information				
Audio codec	Realtek ALC255	Realtek ALC255	Realtek ALC255	Realtek ALC255
Audio features	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)
Display				
Display	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd
Display notes	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.
Sensors	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass
Aspect ratio	16:9	16:9	16:9	16:9
Brightness - typical	400 cd	400 cd	400 cd	400 cd
Contrast - typical	700:1	700:1	700:1	700:1
Digitizer / Touch Technology	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen
Ambient light sensor	Integrated	Integrated	Integrated	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight
Viewing angle (h/v) - typical	178°/178°	178°/178°	178°/178°	178°/178°

Graphics		
TFT resolution (HDMI)	up to 4,096 × 2,160	up to 4,096 × 2,160
TFT resolution (VGA)	1,920 x 1,080 pixel	1,920 x 1,200 pixel
Max. resolution external display	4,096 x 2,304 pixel	4,096 x 2,304 pixel
Max. resolution display port	4,096 x 2,304 pixel	4,096 x 2,304 pixel
Graphics brand name	Intel® HD Graphics 620	Intel® HD Graphics 620
Graphics features	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)
Graphics notes	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system

Interfaces	
DC-in	1
Audio: line-out / headphone	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2 (digital)
USB 3.1 Gen1 (USB 3.0) total	1 (Anytime USB-charge)
VGA	1 (via optional cradle or optional conversion cable)
mini DisplayPort	1
HDMI	1 (via optional cradle or optional DP conversion cable)
Ethernet (RJ-45)	1 (via optional cradle or optional conversion cable)

Interfaces	
Memory card slots	1 microSD up to 2GB microSDHC up to 32GB microSDXC up to 128GB Speed Class: up to UHS-I
SIM card slot	1 (MicroSIM - only for models with integrated 4G/LTE)
Interface Module notes	VGA and HDMI via conversion cables (mini DP to VGA and mini DP to HDMI), Ethernet via conversion cable (USB to RJ-45)
Wireless technologies	
Antennas	2x dual band for WLAN, 2x for 4G/LTE, Bluetooth shared with WLAN, 1 x NFC
Bluetooth	Bluetooth 4.1 LE
Integrated WLAN	Intel Dual Band Wireless-AC8265
WLAN encryption	WEP, WPA, WPA2
WLAN notes	Import and usage according to country-specific regulations.
Integrated LTE or UMTS	LTE Sierra Wireless EM7305 (Cat. 3) (optional)
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.
NFC	optional
GPS	Embedded in 3G/4G module if configured with WWAN
Power supply	
AC adapter	19 V / 65 W (3.42 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	Lithium polymer battery 4-cell, 34 Wh
Runtime 1st battery	up to 10h slate only and 9h incl. keyboard (Productivity Workload MobileMark® 2014)
Battery charging time	~ 3h
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	319 x 9.5 x 201 mm 12.55 x 0.37 x 7.91 inch
Weight	from 830 g slate only / 1170g incl. keyboard
Weight (lbs)	slate only from1,83 lbs / incl. keyboard 2,58 lbs
Weight notes	Weight may vary depending on actual configuration (including battery pack)
Operating ambient temperature	Running: 5 - 35 °C; Packed -15 - 60 °C
Operating relative humidity	Running: 20 - 85%; Packed 8 - 85% (relative humidity, non-condensing)
Product	STYLISTIC R727
Germany	GS (planned)
Europe	CE! EN 60950
Global	ENERGY STAR® 6.1 EPEAT® Gold (dedicated regions) (planned) RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) IT-Eco-Declaration Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software	
Additional software (preinstalled)	Waves MaxxAudio (audio enhancer) LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver and utility tool) Microsoft Office (buy license to activate the pre-installed Microsoft Office) McAfee Internet Security and Antivirus Software (60 days trial version)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)

Manageability	
Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability

Security				
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)
User Security	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

Cradle STYLISTIC R series		The cradle for STYLISTIC R series allows you switch from mobile to desktop productivity mode in one click. Enjoy a complete desktop experience with a FUJITSU display, wireless mouse and keyboard or magnetic keyboard and work comfortably on spreadsheets or presentations. Available ports: HDMI, DisplayPort, VGA, 2x USB 3.0, LAN, Audio (1x in / 1x out), DC-In, Kensington lock support.	Order Code: S26391-F2167-L100

			Order Code: S26391-F6097-L363
Active Pen for STYLISTIC R726		Annotate and fill in forms on your tablet with the premium, real size FUJITSU Active Pen. Navigate, erase and right-click with the function button. Includes a battery and a pen holder to attach to the keyboard or tablet.	Order Code: S26391-F2169-L100
VGA Conversion Adapter (Mini Display Port to VGA)		Connect and present on demand from your STYLISTIC Tablet with the FUJITSU VGA Conversion Cable. From the mini Display Port on your Tablet to the VGA port on the projector or display. (Picture similar to product)	Order Code: S26391-F2169-L200
HDMI Conversion Adapter (mini DP to HDMI)		The FUJITSU HDMI Conversion Cable lets you connect your STYLISTIC tablet to projectors and screens that have a modern HDMI interface. (Picture similar to product)	Order Code: S26391-F2169-L300
LAN Conversion Cable (USB to LAN)		The FUJITSU LAN Conversion Cable allows you to connect your STYLISTIC tablet to a wired network connection. (Picture similar to product)	Order Code: S26391-F2169-L400

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Tablet STYLISTIC R727, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about FUJITSU Tablet STYLISTIC R727, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/tabletpc

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT
Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2017-03-23 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH