

CorePro LEDcapsule LV

CorePro LEDcapsuleLV 2-20W G4 827 D

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Cap-Base	G4 [G4]
Bulb Shape	Capsule
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	2-20W

Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	200 lm
Luminous Flux (Rated) (Nom)	200 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	100.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Power (Rated) (Nom)	2 W
Lamp Current (Nom)	220 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	12 V

Temperature	
T-Case Maximum (Nom)	84 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A++
Energy Consumption kWh/1000 h	3 kWh

Product Data	
Full product code	871869657865000
Order product name	CorePro LEDcapsuleLV 2-20W G4 827 D

CorePro LEDcapsule LV

EAN/UPC - Product	8718696578650
Order code	929001235302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material Nr. (12NC)	929001235302
Net Weight (Piece)	0.012 kg

Dimensional drawing



Capsule 12V 2W-20W 200lm 2700K G4 D

Product	D	C
CorePro LEDcapsuleLV 2-20W G4 827 D	17 mm	48 mm

Photometric data

General Uniform Lighting

G4-Capsule 2W 2700K 9290012353

1 x 200 lm

Polar intensity diagram



Quantity estimation diagram



Light output ratio	1.00
Service upward	0.50
Service downward	0.50
CIE flux code	7 31 61 50 96

Utilisation factor table

Room Index k	Reflectances (%) for ceiling, walls and working plane (CIE)										
	0.80	0.80	0.70	0.70	0.70	0.50	0.50	0.30	0.30	0.00	
	0.50	0.50	0.50	0.50	0.30	0.30	0.10	0.30	0.10	0.00	
	0.30	0.10	0.30	0.20	0.10	0.10	0.10	0.10	0.10	0.00	
0.60	0.29	0.27	0.26	0.25	0.25	0.17	0.14	0.09	0.10	0.07	0.01
0.80	0.37	0.35	0.33	0.32	0.31	0.23	0.19	0.14	0.14	0.10	0.04
1.00	0.44	0.41	0.39	0.38	0.37	0.29	0.23	0.18	0.18	0.14	0.06
1.25	0.51	0.46	0.46	0.44	0.42	0.34	0.28	0.23	0.22	0.17	0.08
1.50	0.56	0.51	0.51	0.49	0.46	0.39	0.32	0.26	0.25	0.20	0.11
2.00	0.65	0.58	0.58	0.55	0.53	0.46	0.37	0.32	0.30	0.26	0.14
2.50	0.71	0.63	0.64	0.60	0.57	0.51	0.42	0.37	0.33	0.30	0.17
3.00	0.76	0.66	0.68	0.64	0.61	0.54	0.45	0.41	0.36	0.33	0.20
4.00	0.82	0.71	0.74	0.69	0.65	0.60	0.50	0.46	0.40	0.37	0.24
5.00	0.87	0.74	0.78	0.73	0.68	0.64	0.53	0.50	0.43	0.40	0.26

Ceiling mounted

Luminance Table

Plane / Cone	0.0	15.0	30.0	45.0	60.0	75.0	90.0
45.0							
50.0							
55.0							
60.0	Cannot draw luminance table: the apparent area equals zero.						
65.0							
70.0							
75.0							
80.0							
85.0							
90.0							

(cd/m²)

SL22224-#1

2016-05-17

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.