

Cleanroom LED CR250B

CR250B LED35S/840 PSU W60L60 IP65

LED GreenLine 3500 lm - 840 neutral white - Power supply unit - Dust penetration-protected, jet-proof

In applications where hygiene is crucially important, such as hospitals and food production facilities, customers want proven IP65- and IP54-rated luminaires that are safe to use and are an economical investment. This family of fixtures represents an affordable solution: the Philips LED engine delivers reliable, high-quality light, and the flexible mounting possibilities mean that this family can be used in a wide range of applications. The fixtures are also compliant with all relevant standards (CE, EMC, RoHS).

Product data

General Information	
Number of light sources	2 [2 pcs]
Lamp family code	GRN35 [LED GreenLine 3500 lm]
Light source colour	840 neutral white
Light source replaceable	Yes
Number of gear units	1 unit
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Optic type	No [-]
Optical cover/lens type	GC-D [Clear glass with diffuser foil]
Luminaire light beam spread	110°
Control interface	-
Connection	SCREW [Screw connector]
Cable	-
Protection class IEC	Safety class II (II)
Colour	White

Glow-wire test	850/30 [Temperature 850 °C, duration 30 s]
Flammability mark	D [For mounting on easily flammable surfaces]
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB	24
RoHS mark	RoHS mark

Operating and Electrical	
Input voltage	220-240 V
Input frequency	50-60 Hz
Power consumption when dimming	3 W
Inrush current	13 A
Inrush time	270 ms

Cleanroom LED CR250B

Power factor (min.)	0.9

Controls and Dimming

Dimmable	No

Mechanical and Housing

Housing material	Steel
Optical cover/lens material	Tempered glass
Fixation material	Stainless steel
Optical cover/lens finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	135 mm
Length	595 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]

Initial Performance (IEC Compliant)

Initial luminous flux	3500 lm
Luminous flux tolerance	+/-5%
Initial LED luminaire efficacy	88 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	>80
Initial chromaticity	(0.38, 0.38) SDCM <4
Initial input power	40 W
Power consumption tolerance	+/-5%

Over Time Performance (IEC Compliant)

Driver failure rate at 5,000 hours	1 %
Median useful life L70B50	50000 h
Median useful life L80B50	30000 h
Median useful life L90B50	15000 h

Application Conditions

Ambient temperature range	-20 to +40 °C
Average ambient temperature	25 °C
Maximum dimming level	Not applicable
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871869607283700
Order product name	CR250B LED35S/840 PSU W60L60 IP65
EAN/UPC – product	8718696072837
Order code	07283700
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910503910167
Net weight (piece)	9.000 kg



Dimensional drawing



Cleanroom CR150B/CR250B



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.