Product data sheet
Characteristics

NSYOPB9U5F
Wall-Mounted Open Box 9U W600 D500 Fixed 19" Glazed Door R7035



Main

Range of product	Actassi OPB
Product or component type	19" enclosure
Device application	Cabling
Enclosure mounting	Wall mounted
Product specific application	To mount 19" equipment To protect network connectivity equipment
Enclosure type	Open box
Colour tint	Light grey (RAL 7035)

Complementary

Number of rack unit	9U
For enclosure nominal dimensions	515 mm 600 mm 500 mm
Device composition	3 x cable entries 1 x front glazed door 1 x open structure 2 x side panels 2 x front 19" uprights
Permanent permissible load	Static : 50 kg By unit : 3 kg
Door type	Front glazed door - with 1 point locking system (key: 333) - reversible opening at 180 °
Provided equipment	2 x fixed 19" uprights recessed of 120 mm from the front (pitch 25 mm)
Number of cut-out	1 cut-out top 1 cut-out bottom 1 cut-out side
Accessibility for operation	Rear Side Front
Removable parts	Top blanking plate Bottom blanking plate Rear blanking plate Side panels removable toolless

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Front door removable toolless
Material	Structure : sheet steel Door : sheet steel Upright : galvanized steel Door : sekurit glass
Surface finish	Epoxy-polyester powder

Environment

Standards	EIA-310D IEC 60297-3-100
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations Product environmental

Contractual warranty

Warranty period	18 months