Product data sheet
Characteristics

DC6PCURJ05GYM
Category 6, Patch Cord, UTP, 5M, Grey



Main

Range	Digilink
Product or component type	Patch cord
Cable shielding type	UTP
Colour tint	Grey

Complementary

Type of cable	4 twisted-pairs cable
Communication network category	6
Connector type	RJ45
Material	PC (polycarbonate) plug
AWG gauge	AWG 23 stranded cable
Insulation resistance	>= 500 mOhm @ 500 V DC
Contacts material	Gold over nickel
[In] rated current	<= 1.5 A
Contact resistance	<= 20 mOhm
[Ue] rated operational voltage	< 72 V DC
Cable length	5 m

Environment

Flame retardance	UL 94 V-0
Standards	ANSI/TIA-568-C.2 ISO/IEC 11801 class E
Product certifications	UL listed UL/ETL verified

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months