Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Supplier name or trademark	Candy
Product name / Commercial code	CMB955X
Annual Energy Consumption, AEChood (kWh/a)	76.7
Energy Efficiency class (2010/30/EC)	C
Energy Efficiency Index, EEI	74.2
Fluid Dynamic Efficiency (FDEhood)	18.7
Fluid Dynamic Efficiency class	C
Lighting Efficiency (Lehood)	18
Lighting Efficiency class	C
Grease Filtering Efficiency	83.3
Grease Filtering Efficiency class	C
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	620
Air flow at at intensive or boost setting (m3/h)	
Airborne acoustical A-weighted sound power emissions at Min/Max	67
Airborne acoustical A-weighted sound power emissions at intensive	
Power consumption in off mode (Po) (W)	0.27
Power consumption in standby mode (Ps) (W)	
Time increase factor, f	1.3
Measured air flow rate at best efficiency point, QBEP (m3/h)	338
Measured air pressure at best efficiency point, PBEP (Pa)	312
Measured electric power input at best efficiency point, WBEP (W)	157
Nominal power of the lighting system, WL (W)	3
Average illumination of the lighting system on the cooking surface,	54