EME Series Commercial LED LCD Displays

65"	EM65E
75"	EM75E

SAMSUNG



A clear, simple solution for meeting rooms

EME Series 65"/75" displays with integrated HDBaseT receivers

Improve the clarity of meetings and huddle rooms with the Samsung EME Series displays. Featuring embedded HDBaseT receivers, they're simple ways of taking advantage of uncompressed content over long distance. Just connect a single Ethernet LAN cable, and you're ready to go. Installation is simple and clean, content is clear and sharp. With nothing lost in the translation, they're the ideal ways to enhance collaboration and communication.

Key features

Built-in* HDBaseT receiver

The built-in HDBaseT receiver on the EME Series allows you to take full advantage of HDBaseT, while simplifying installation. Connectivity is simple, and cable clutter is eliminated.

Connect through a single LAN cable

With an integrated HDBaseT receiver, the EME Series displays receive uncompressed Full HD multimedia content. The AV signal and control signal travel through a single LAN Ethernet cable. Content suffers no degradation, and the single cable allows a clean installation.

Meeting room console*

The included meeting room console serves as a table top remote control for volume change, source change and power ON/OFF.

Full HD and built-in speakers

The EME Series is meeting room-ready with Full HD resolution and built-in 10W x 2 stereo speakers. Images are clear, crisp and colorful. Audio is full and rich.

*Requires Samsung meeting box: SBB-MT12EA to work properly.

Contact us
1-866-SAM4BIZ
samsung.com/business
samsung.com/b2bdigitalsignage

Follow us
youtube.com/samsungbizusa
@SamsungBizUSA

Samsung EME Series commercial LED LCD displays with integrated HDBaseT receivers





			EM65E	EM75E
Panel	Diagonal Size		65"	75"
	Type		60Hz LED BLU	60Hz LED BLU
	Resolution		1920 x 1080 (16:9)	1920 x 1080 (16:9)
	Brightness (Typ.)		400 nits	400 nits
	Contrast Ratio (Typ.)		4000:1	5000:1
	Viewing Angle (H / V)		178:178	178:178
	Response Time (G-to-G)		6ms	4ms
	Orientation		Landscape / Portrait	Landscape / Portrait
Sound	Speaker Type		Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)
Connectivity	Input	RGB	Analog D-SUB, DVI-D	Analog D-SUB, DVI-D
		Video	CVBS, Component, HDMI, HDBT	CVBS, Component, HDMI, HDBT
		Audio	Stereo Mini Jack	Stereo Mini Jack
		USB	USB Player	USB Player
	Output	Audio	Stereo Mini Jack	Stereo Mini Jack
	External Control		RS232C (In / Out) thru Stereo Jack	RS232C (In / Out) thru Stereo Jack
	External Sensor		Yes	Yes
Power	Type		Internal	Internal
	Power Supply		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	Power Consumption	Max [W / H]	253	308
		Typical [W / H]	215	260
		Sleep Mode	Less than 0.5W	Less than 0.5W
		Off Mode	Less than 0.5W	Less than 0.5W
Dimensions	Set In. (WxHxD)		57.7" x 33.3" x 2.2"	65.9" x 37.7" x 3.4" (Except Handle 2.2")
	Package In. (WxHxD)		62.9" x 38.5" x 11.2"	71.2" x 42.7" x 9.8"
	Bezel Width (mm)		18.0mm (Bottom 23.5mm)	12mm (Bottom 17.3mm)
Weight	Set		60.4 lbs.	75.1 lbs.
	Package		78 lbs.	97.2 lbs.
Features	VESA Mount		400 x 400mm	400 x 400mm
	Stand Type		Foot Stand (Optional)	Foot Stand (Optional)
	Special		Built in Speaker (10W + 10W), PIP / PBP, Narrow Bezel, Light Weight, RS232 In / Out, 1 D-Sub, 1 HDMI	Built in Speaker (10W + 10W), PIP / PBP, Narrow Bezel, Light Weight, RS232 In / Out, 1 D-Sub, 1 HDMI
Environmental Conditions	Operating Temperature		0ºC ~ 40ºC	0ºC ~ 40ºC
	Operating Humidity		10 ~ 80%	10 ~ 80%
Accessories	Included		Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries
	Optional	Stand	STN-L6500E	STN-L7585F
		Mount	WMN6575SD	WMN6575SD
		Media Player	SBB-DA / DI	SBB-DA / DI
		Meeting Room Box & Console	SBB-MT12EA	SBB-MT12EA
Green Management	Emission Standard		EMC	EMC
	ENERGY STAR Compliant		N/A	N/A
	RoHS Compliant		Yes	Yes
	Packaging Recyclability		Packing Materials Recyclable	Packing Materials Recyclable
Service	Standard Warranty		3 Years Onsite (Parts / Labor / Backlight)	3 Years Onsite (Parts / Labor / Backlight)

CONNECTIVITY

1. HBDT In
2. USB (5V, 1.5A)
3. DVI In / MagicInfo In
4. HDMI
5. RGB In
6. RS232C In
7. RS232C Out
8. RGB / DVI / HDMI / AV / Component / Audio In
9. Audio Out
10. AV In / Video / Component In
11. IR / Ambient Sensor In









MEETING ROOM BOX & CONSOLE (SBB-MT12EA)		
Model	Part Number	SBB-MT12EA
Connectivity	Ethernet	10/100Mbps (MDC)
	USB	USB Port x 1 (S/W Update Only)
	Output	DVI Out, RJ-45, RS232 In (Stereo), IR In
	Others	HDMI1, HDMI2, HDBT Out
Power	Type	Adapter
	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	Power Consumption	17W (Max) / 10W (Typical) / 15W (Rating)
Dimensions	Set	8.76" x 5.5" x 1.25"
	Package	13.2" x 11.2" x 2.3"
Weight	Set	3.3 lbs.
	Package	8.2 lbs.
Environmental Conditions	Operating Temperature	10ºC~ 40ºC
	Operating Humidity	10 ~ 80%
Accessories	Included	User Manual, Adaptor, Power Cord, DVI to HDMI Cable, External IR Sensor, Meeting Console

Learn more samsung.com/business insights.samsung.com samsung.com/b2bdigitalsignage

Product support 1-866-SAM4BIZ 1-800-SAMSUNG

Follow us youtube.com/samsungbizusa @SamsungBizUSA

SAMSUNG

©2016 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. Simulated screen images. All brand, product, service names and logos are trademarks and or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. LFD-EMESERIESDSHT-OCT16T